

BUS RAPID TRANSIT PROJECT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS FEDERAL AID PROJECT NO. CML-5008(149) CITY OF STOCKTON PROJECT NO. PW1516

PREPARED FOR: CITY OF STOCKTON

NOTES, LEGEND AND ABBREVIATIONS 3. DT-1 DETAILS 4. DT-2 DETAILS 5. DT-3 DETAILS 6. DT-4 DETAILS 7. SY-1 SYSTEM DIAGRAM (CCTV VIDEO) 8. SY-2 SYSTEM DIAGRAM (FIBER SWITCHES) 16. TS-1 WEBER AVE AT CENTER ST TRAFFIC SIGNAL MODIFICATION 17. TS-2 WEBER AVE AT EL DORADO ST TRAFFIC SIGNAL MODIFICATION 18. TS-3 WEBER AVE AT SAN JOAQUIN ST TRAFFIC SIGNAL MODIFICATION 19. TS-4 WEBER AVE AT SUTTER ST TRAFFIC SIGNAL MODIFICATION 20. TS-5 MINER AVE AT CALIFORNIA ST TRAFFIC SIGNAL MODIFICATION MINER AVE AT STANISLAUS ST TRAFFIC SIGNAL MODIFICATION 22. TS-7 MINER AVE AT WILSON WAY TRAFFIC SIGNAL MODIFICATION FILBERT ST AT MYRTLE ST (WEBER AVE) TRAFFIC SIGNAL MODIFICATION TS-13 FILBERT ST AT MYRTLE ST (SR4 WB) TRAFFIC SIGNAL MODIFICATION FILBERT ST AT MARKET ST (SR4 EB) TRAFFIC SIGNAL MODIFICATION TS-14 FILBERT ST AT LAFAYETTE ST TRAFFIC SIGNAL MODIFICATION 30. TS-14B FILBERT ST AT LAFAYETTE ST TRAFFIC SIGNAL SCHEDULE 31. TS-15 MAIN ST AT FILBERT ST TRAFFIC SIGNAL MODIFICATION 32. TS-15B MAIN ST AT FILBERT ST TRAFFIC SIGNAL SCHEDULE 33. TS-16 MAIN ST AT GOLDEN GATE AVE TRAFFIC SIGNAL MODIFICATION 34. TS-17 MAIN ST AT NETHERTON AVE TRAFFIC SIGNAL MODIFICATION 35. EQ-1 SUMMARY EQUIPMENT LIST





- CA: 1−800−227−2600**-**

CALL TWO WORKING

SHEET INDEX

APPROVED BY DATE Oakland, California 94612 Phone: (510) 625-0712

PROJECT LOCATION MAP NOT TO SCALE

DESIGNED UNDER THE SUPERVISION OF: 12/19/2019 No. 048732 DATE KEVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS COVER SHEET

> DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

STOCKTON, CALIFORNIA

5365C

GENERAL NOTES

- 1. THESE PLANS ARE HEREBY MADE PART OF THE CONTRACT SPECIFICATIONS FOR THIS PROJECT. THESE PLANS SHALL BE ACCOMPANIED BY SEPARATE 1. POLES, DETECTOR HAND HOLES, INDUCTIVE LOOPS AND CONTROLLER CABINET LOCATIONS SHALL BE LOCATED IN THE FIELD SET OF SPECIAL PROVISIONS. THE CONTRACTOR SHALL NOT PROCEED WITH ANY WORK CALLED FOR ON THESE PLANS UNTIL THE CITY ENGINEER'S SIGNATURE OF APPROVAL IS AFFIXED HEREON AND ALL APPLICABLE PERMITS HAVE BEEN OBTAINED. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL PERMITS AND LICENSES REQUIRED TO COMPLETE THE PROJECT. AN APPROVED SET OF PLANS SHALL BE ON THE JOB SITE DURING ANY CONSTRUCTION.
- 2. ALL WORK AND MATERIAL EMBRACED IN THIS PROJECT SHALL BE DONE IN ACCORDANCE WITH APPLICABLE PROVISIONS OF THE CITY OF STOCKTON DEPT. OF PUBLIC WORKS, STANDARD SPECIFICATIONS AND PLANS, THE LATEST EDITIONS OF CALTRANS STANDARD PLANS AND SPECIFICATIONS, AND IN ACCORDANCE WITH THE SPECIAL PROVISIONS OF THIS PROJECT.
- 3. THE CONTRACTOR SHALL ASSUME SOLE AND COMPLETE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THIS PROJECT, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY: THAT THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS: AND THAT THE CONTRACTOR SHALL DEFEND, INDEMNIFY AND HOLD THE OWNER AND ENGINEER HARMLESS FROM ANY AND ALL LIABILITY. REAL OR ALLEGED IN CONNECTION WITH THE PERFORMANCE OF WORK ON THIS PROJECT. EXCEPT FOR LIABILITY ARISING FROM THE SOLE NEGLIGENCE OF THE OWNER OR ENGINEER.
- 4. THE CONTRACTOR SHALL MAKE AN ON-SITE INSPECTION PRIOR TO PROVIDING ANY BIDS TO DETERMINE ANY AND ALL ITEMS NECESSARY TO PERFORM A COMPLETE AND ACCEPTABLE JOB.
- 5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPORTING ALL CONFLICTS, ERRORS, OMISSIONS, ETC. TO THE ENGINEER IMMEDIATELY UPON DISCOVERY. IF SO DIRECTED BY THE ENGINEER, THE CONTRACTOR SHALL STOP WORK UNTIL REMEDIAL ACTION CAN BE TAKEN. ANY COSTS RESULTING FROM THE CONTRACTOR'S FAILURE TO REPORT OR FAILURE TO STOP WORK, AS DIRECTED, WILL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 6. THE CONTRACTOR SHALL CONTACT THE CITY OF STOCKTON PUBLIC WORKS DEPARTMENT (209-937-8381) FOR A PRE-CONSTRUCTION CONFERENCE AFTER THE AWARD OF CONTRACT AND AT LEAST THREE (3) WORKING DAYS IN ADVANCE OF WORK.
- 7. THE CONTRACTOR SHALL BE RESPONSIBLE TO NOTIFY PG&E AND OTHER UTILITY COMPANIES PRIOR TO START OF WORK. THE CONTRACTOR SHALL CALL USA (800-227-2600) 48 HOURS PRIOR TO ANY EXCAVATION.
- 8. THE CONTRACTOR SHALL, BY HAND, POTHOLE EXISTING UTILITIES TO VERIFY LOCATION PRIOR TO CONSTRUCTION.
- 9. EXISTING UTILITIES INCLUDING MANHOLES, STORM DRAIN CATCH BASINS, VALVES, BOXES, ETC., SHALL BE PROTECTED IN PLACE AND REMAIN OPERATIONAL AT ALL TIMES UNLESS NOTED OTHERWISE.
- 10. THE LOCATIONS OF ALL UNDERGROUND FACILITIES SHOWN ON THIS PLAN ARE APPROXIMATE. A REASONABLE EFFORT HAS BEEN MADE TO LOCATE AND DELINEATE ALL UNDERGROUND FACILITIES; HOWEVER, THE CONSULTANT ENGINEER ASSUMES NO LIABILITY FOR THE ACCURACY OR COMPLETENESS OF THE EXISTING FACILITIES SHOWN HEREON OR FOR THE EXISTENCE OF OTHER UNDERGROUND UTILITIES OR OBJECTS WHICH MAY BE DISCOVERED BUT ARE NOT SHOWN ON THESE PLANS. THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING FACILITIES AND IMMEDIATELY NOTIFY THE ENGINEER IF ANY SUCH FACILITIES INTERFERE WITH THE CONSTRUCTION OF IMPROVEMENTS. CALL U.S.A. 1-800-227-2600. THE CONTRACTOR SHALL STOP WORK AROUND THE AREA OF CONFLICT UNTIL HE IS DIRECTED BY THE ENGINEER TO CONTINUE.
- 11. THE CONTRACTOR SHALL COMPLY WITH THE REQUIREMENTS OF THE STATE WATER RESOURCES CONTROL BOARD (SWRCB) ORDER NO. 2009-0009-DWQ. THE CONTRACTOR SHALL IMPLEMENT AND MONITOR A STORM WATER POLLUTION PREVENTION PLAN IN ACCORDANCE WITH THE SWCRB REGULATIONS. THE CONTRACTOR SHALL FOLLOW THE REQUIREMENTS IN THE STORMWATER BEST MANAGEMENT PRACTICE CONSTRUCTION HANDBOOK WHICH IS PREPARED BY THE CALIFORNIA STORMWATER QUALITY ASSOCIATION (CASQA) AND ADOPTED BY THE STATE AND THE CITY. IT IS PROHIBITED TO DISCHARGE ANYTHING EXCEPT CLEAN WATER INTO THE STORM DRAIN SYSTEM.
- 12. ATTENTION IS CALLED TO: SECTION 1540(A) (1) OF THE CONSTRUCTION SAFETY ORDERS (TITLE 25. 8 CALIFORNIA ADMINISTRATION CODE SECTION 1540), ISSUED BY THE OCCUPATIONAL SAFETY AND HEALTH STANDARDS (OSHA) BOARD PURSUANT TO THE CALIFORNIA OCCUPATIONAL SAFETY AND HEALTH (CAL-OSHA) ACT OF 1973, AS AMENDED, WHICH STATES:

"PRIOR TO OPENING AN EXCAVATION, EFFORT SHALL BE MADE TO DETERMINE WHETHER UNDERGROUND INSTALLATION I.E., SEWER, WATER, FUEL ELECTRIC LINES, ETC.., WILL BE ENCOUNTERED AND, IF SO, WHETHER SUCH UNDERGROUND INSTALLATIONS ARE LOCATED. WHEN THE EXCAVATION APPROACHES THE APPROXIMATE LOCATION OF SUCH AN INSTALLATION, THE EXACT LOCATION SHALL BE DETERMINED BY CAREFUL PROBING OR HAND DIGGING AND WHEN IT IS UNCOVERED, ADEQUATE PROTECTION SHALL BE PROVIDED FOR THE EXISTING INSTALLATION. ALL KNOWN OWNERS OF UNDERGROUND FACILITIES IN THE AREA CONCERNED SHALL BE ADVISED OF PROPOSED WORK AT LEAST 48 HOURS PRIOR TO THE START OF ACTUAL EXCAVATION."

- 13. THE CONTRACTOR SHALL PROVIDE SHORING, BRACING, SLOPING OR PROVISIONS TO PROTECT WORKERS FOR ALL AREAS TO BE EXCAVATED TO A DEPTH OF FIVE FEET OR MORE. SAID PROTECTION TO BE DONE IN ACCORDANCE WITH THE REQUIREMENTS OF LOCAL, STATE, AND FEDERAL REGULATIONS (CAL-OSHA, OSHA).
- 14. THE CONTRACTOR SHALL PROVIDE ADEQUATE TRAFFIC CONTROLS AND SHALL SUBMIT TO THE CITY TRAFFIC ENGINEERING DIVISION A TRAFFIC CONTROL PLAN (TCP) FOR EACH PHASE OF WORK. THE TCP MUST BE APPROVED BY THE CITY TRAFFIC ENGINEER PRIOR TO THE START OF CONSTRUCTION.
- 15. PRIOR TO BEGINNING ANY WORK ON EXISTING STREETS, ADVANCE WARNING SIGNS SHALL BE INSTALLED. TRAFFIC CONTROL SHALL BE PROVIDED IN ACCORDANCE WITH PART 6 OF THE 2014 CALIFORNIA MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (CA MUTCD), AND ANY ADDITIONAL CITY REQUIREMENTS. FAILURE TO COMPLY MAY RESULT IN IMMEDIATE STOPPAGE OF WORK UNTIL THE PROPER TRAFFIC CONTROL IS IN ORDER.
- 16. TRAFFIC CONTROL MAINTENANCE AND OPERATION SHALL COMPLY WITH THE FOLLOWING STATE STANDARD SPECIFICATION SECTIONS:

SECTION 7-1.04 "PUBLIC SAFETY"

SECTION 7-1.03 "PUBLIC CONVENIENCE"

SECTION 12 "TEMPORARY TRAFFIC CONTROL"


- 17. THE CONTRACTOR SHALL PROVIDE ALL WARNING LIGHTS, SIGNS, BARRICADES, FLAGMEN OR OTHER DEVICES NECESSARY TO PROVIDE FOR PUBLIC
- 18. ALL EXISTING SIGNS AND POSTS SHALL REMAIN UNLESS OTHERWISE NOTED.
- 19. THE CONTRACTOR SHALL BACKFILL WITH CUTBACK EACH NIGHT ANY AREAS NOT COMPLETED TO ITS FINISHED STATE. ALL EXCAVATED AREAS SHALL BE PROTECTED FROM PEDESTRIANS, BICYCLISTS AND VEHICULAR TRAFFIC AT ALL TIMES.
- 20. ALL NEW FLATWORK SHALL BE DRILLED AND DOWELED AND/OR KEYED INTO EXISTING FLATWORK IN ACCORDANCE WITH CITY OF STOCKTON STANDARD PLANS AND SPECIFICATIONS.
- 21. ALL EXISTING PUBLIC AND PRIVATE IMPROVEMENTS, INCLUDING ALL CURBS, GUTTERS, SIDEWALKS, IRRIGATION, LANDSCAPING, AND FENCES, THAT BECOME DAMAGED DURING CONSTRUCTION SHALL BE COMPLETELY RESTORED TO THE SATISFACTION OF THE ENGINEER. AT CONTRACTOR'S SOLE
- 22. THE CONTRACTOR SHALL REPLACE ANY PAVEMENT DELINEATION OR TRAFFIC MARKINGS REMOVED OR DAMAGED IN THE COURSE OF THIS WORK. PRIOR TO ANY REMOVAL, THE CONTRACTOR SHALL DOCUMENT THE TYPE AND LOCATION OF THE PAVEMENT DELINEATION / MARKINGS.
- 23. THE CONTRACTOR SHALL RETURN SALVAGEABLE EQUIPMENT (AS NOTED IN THE PLANS) TO THE CITY OF STOCKTON CORPORATION YARD AT 1465 SOUTH LINCOLN STREET, STOCKTON, CALIFORNIA, 95206. CONTRACTOR SHALL NOTIFY THE CORP. YARD AT (209) 937-7406 A MINIMUM OF THREE (3) WORKING DAYS IN ADVANCE OF DELIVERY.
- 24. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COMPACTION TESTING AND SHALL PROVIDE TO THE CITY ALL COMPACTION TEST RESULTS SHOWING THAT THE CITY'S MINIMUM COMPACTION STANDARDS HAVE BEEN ACHIEVED.

TRAFFIC SIGNAL AND ELECTRICAL NOTES

- BY THE CONTRACTOR WITH THE APPROVAL OF THE CITY TRAFFIC ENGINEER. TYPICALLY, DETECTOR HANDHOLES SHOULD BE INSTALLED ON LANE LINES.
- 2. CONTRACTOR SHALL MEET GENERAL ORDER (G.O.) 95 REQUIREMENTS AND LOCATE FOUNDATIONS SO AS TO PROVIDE A MINIMUM OF 6' RADIAL CLEARANCE FROM ALL EQUIPMENT TO OVER HEAD POWER LINES (PRIMARY) AND A MINIMUM OF 3' RADIAL CLEARANCE TO COMMON NEUTRAL LINES. SIGNAL POLES SHALL BE LOCATED TO PROVIDE A MINIMUM OF 10' OF RADIAL CLEARANCE TO PRIMARY LINES. CONTRACTOR SHALL CONTACT PG&E FOR ANY WORK TO BE DONE WITHIN 10' RADIAL CLEARANCE ZONE. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY COSTS ASSOCIATED WITH WORKING WITHIN THE 10' RADIAL CLEARANCE ZONE.
- 3. SIDEWALK REMOVAL SHALL BE TO THE NEAREST SCORE MARK OR AS DETERMINED BY THE ENGINEER. CONTRACTOR SHALL NEATLY SAW-CUT CONCRETE WHERE PULL BOXES ARE TO BE PLACED AND SHALL RESTORE THE SLAB TO MATCH THE EXISTING CONDITION.
- 4. ALL PULL BOXES SHALL BE STATE STANDARD NUMBER 5 UNLESS OTHERWISE NOTED ON PLAN.
- 5. CONDUIT ROUTING IS SHOWN DIAGRAMMATICALLY, CONTRACTOR SHALL LAYOUT RUNS TO SUIT FIELD CONDITIONS AND THE COORDINATION REQUIREMENTS OF UTILITIES OR ANY OTHER TRADES, AND TO THE SATISFACTION OF THE CITY OF STOCKTON. UPON COMPLETION OF CONDUIT INSTALLATION. THE ACTUAL LOCATION OF THE CONDUITS SHALL BE NOTED ON AN AS-BUILT SET OF PRINTS AND FURNISHED TO
- 6. INSTALLATION OF NEW CONDUCTORS INTO EXISTING CONDUIT SHALL BE IN ACCORDANCE WITH SECTION 77-1.12 OF THE SPECIAL PROVISIONS. PRIOR TO INSTALLATION OF NEW CONDUCTORS/CABLES IN EXISTING CONDUITS, THE CONTRACTOR SHALL USE CABLE LOOSENER TO LOOSEN EXISTING CABLES AND CONDUCTORS IN THE CONDUITS. THE CONTRACTOR SHALL ALSO USE PULLING LUBRICANT FOR PULLING WIRES, AND A PULL TAPE CONFORMING TO THE PROVISION DESCRIBED UNDER "CONDUIT", ELSEWHERE IN THE SPECIAL PROVISIONS.
- 7. LABEL PEDESTRIAN AND SIGNAL COMMONS SEPARATELY IN THE CONTROLLER CABINET.
- 8. CONTRACTOR SHALL INSTALL A PHOTOELECTRIC CONTROL UNIT IN EACH NEW SERVICE CABINET. A SECONDARY PHOTOELECTRIC UNIT (PEU) SHALL BE INSTALLED ON SIGNAL OR LIGHTING POLE NEAREST TO THE SERVICE CABINET. THE SECONDARY PEU SHALL BE WIRED AND TESTED. ONCE TEST IS ACCEPTABLE, THEN PERMANENT CONNECTION TO PEU AND SERVICE CABINET SHALL BE MADE.
- 9. ALL INFRARED EMERGENCY VEHICLE PREEMPTION (EVP)/TRANSIT SIGNAL PRIORITY (TSP) DETECTORS SHALL BE MOUNTED VERTICALLY.
- 10. THE CONTRACTOR SHALL VERIFY THE LOCATION OF ALL EXISTING FIBER OPTIC CABLE AND PROTECT IN PLACE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SECTION 77-1.24 (EX. FIBER) OF THE SPECIAL PROVISIONS.
- 11. EXISTING TRAFFIC SIGNAL SYSTEMS SHALL BE KEPT IN EFFECTIVE OPERATION DURING THE PROGRESS OF THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE MAINTENANCE OF THE ENTIRE EXISTING SIGNAL SYSTEM (AT EACH PROJECT TRAFFIC SIGNAL) FROM THE FIRST DAY CONTRACTOR STARTS WORKING ON THE PROJECT TO THE FINAL ACCEPTANCE.
- 12. THE CONTRACTOR SHALL NOTIFY THE ENGINEER AT LEAST THREE (3) WORKING DAYS IN ADVANCE OF ANY REQUESTED SIGNAL SHUT-DOWN FOR REPLACEMENT OF THE CONTROLLER CABINET ASSEMBLY, RE-WIRING OF THE TRAFFIC SIGNAL, ETC. ALL REQUESTED SIGNAL SHUT-DOWNS ARE SUBJECT TO CITY APPROVAL. CONTRACTOR SHALL SUBMIT A TRAFFIC CONTROL PLAN FOR REVIEW AND APPROVAL BY THE CITY TRAFFIC ENGINEERING DIVISION BEFORE SCHEDULING SIGNAL SHUT—DOWN. TRAFFIC SIGNAL SHUT—DOWNS SHALL BE LIMITED TO PERIODS BETWEEN THE HOURS OF 9:00 AM AND 3:30 PM ON WEEKDAYS ONLY.
- 13. FLASHING INDICATIONS SHALL FLASH IN RED ON ALL PHASES.
- 14. ALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEMS SHALL BE MOUNTED 42" MAX FROM THE SIDEWALK TO THE CENTER OF THE PUSH BUTTON



PROJECT INFORMATION SIGN (TO BE INSTALLED AT SIX LOCATIONS) N.T.S.



12/19/2019 KZVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

DESIGNED UNDER THE SUPERVISION OF:



ADA	AMERICANS WITH DISABILITIES ACT	PTZ	PAN-TILT-ZOOM
APS	ACCESSIBLE PEDESTRIAN SIGNAL	RMC	RIGID METAL CONDUIT
BRT	BUS RAPID TRANSIT	SIC	SIGNAL INTERCONNECT CABLE
CCTV	CLOSED CIRCUIT TELEVISION	TSP	TRANSIT SIGNAL PRIORITY
DLC	DETECTOR LEAD-IN CABLE	TYP.	TYPICAL
EVA	PRE-EMPTION CHANNEL A	АВ	ABANDON. IF APPLIED TO CONDUIT, REMOVE CONDUCTORS.
EVB	PRE-EMPTION CHANNEL B		INSTALL PULL BOX IN EXISTING
EVC	PRE-EMPTION CHANNEL C	BC	CONDUIT RUN.
EVD	PRE-EMPTION CHANNEL D	СВ	INSTALL CONDUIT INTO EXISTING PULL BOX.
EVP	EMERGENCY VEHICLE PRE-EMPTION		CONNECT NEW AND EXISTING CONDUIT.
EX.	EXISTING	CC	REMOVE EXISTING CONDUCTORS AND INSTALL CONDUCTORS AS NOTED.
F.O.	FIBER OPTIC		
GRC	GALVANIZED RIGID STEEL CONDUIT	RC	EQUIPMENT OR MATERIAL TO BE REMOVED AND BECOME PROPERTY OF THE CONTRACTOR.
MAX	MAXIMUM		
MIN	MINIMUM	RL	RELOCATE EQUIPMENT.
МТ	EMPTY	RS	REMOVE AND SALVAGE EQUIPMENT.

ABBREVIATIONS

LEGEND

PPB PEDESTRIAN PUSH BUTTON

	LEGEN	<u>ND</u>
PROPOSED	EXISTING	
		CONDUIT
	X	
		- SANITARY SEWER LINE AND MANHOLE
	•	STORM SEWER LINE AND MANHOLE
	W	
	N2	NITROGEN GAS LINE
		- ELECTRICAL LINE
	G	GAS LINE
		TELEPHONE LINE
		- FIBER OPTIC LINE
\boxtimes		TRAFFIC SIGNAL CONTROLLER CABINET
	r T L M	
	 >	
	C3	PULL BOX
•	<♡>	, ,
0	Q	TRAFFIC SIGNAL STANDARD
-	< ⁴	EVP/TSP OPTICAL DETECTOR UNIT
	70 5	UTILITY POLE
	,	FIRE HYDRANT
	\bigcirc	TELEPHONE MANHOLE
	₩V	WATER VALVE
т	7-6	MAST ARM MOUNTED SIGN
		DETECTOR LOOP CABLE
		VIDEO DETECTION ZONE - VEHICLE
		VIDEO DETECTION ZONE - BICYCLE
		GRAPHIC SCALE
		20 0 10 20 40
	•	(IN FEET)
		1 inch = 20 ft.

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS


NOTES, LEGEND AND ABBREVIATIONS

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA DATE: DECEMBER 2019

PW1516 SHEET NO. GN-1CHECKED BY: EKC STOCKTON, CALIFORNIA SHEET 2_ OF 36


5365.1C







5365.2C

SHEET 3 OF 36







NOTES:

- 1. THE MAXIMUM DRAINAGE AREA PER FILTER SHALL BE NO MORE THAN .06 HECTARES (2 ACRES).
- 2. THE FILTER BAG SHALL BE MANUFACTURED FROM UV RESISTANT POLYPROPYLENE NYLON, POLYESTER, OR ETHYLENE FABRIC WITH A MINIMUM TENSILE STRENGTH OF 50 LBS PER LINEAL FOOT. AN EQUIVALENT OPENING SIZE NOT GREATER THAN A 20 SIEVE AND WITH A MINIMUM FLOW RATE OF 40 GALLONS/SQFT.
- 3. THE FILTER BAG MAY BE SUSPENDED FROM OR HELD IN PLACE BY EXISTING INLET GRATE (OR OTHER APPROVED METHOD), PROVIDING NO MODIFICATION OR DRAINAGE SHALL BE DONE TO THE INLET GRATE OR FRAME. THE INLET GRATE SHALL NOT BE CAUSED TO REST MORE THAN 1/2" ABOVE THE INLET FRAME.
- 4. THE FILTER BAG MAY EXTEND TO THE BOTTOM OF THE INLET BOX PROVIDED THE OUTLET PIPE IS UNOBSTRUCTED.
- 5. FLOWS SHALL NOT BE ALLOWED TO BYPASS THE BAG. THE BAG OR IT'S FRAME SHALL CATCH FLOWS AT ALL SIDES OF THE INLET EXCEPT AS SHOWN FOR FLOOD RELEASE.
- 6. INLET FILTER BAGS SHALL BE INSPECTED WEEKLY AND AFTER EACH RAINFALL DURING THE WET SEASON AND MONTHLY DURING THE DRY SEASON. SEDIMENT AND DEBRIS SHALL BE REMOVED BEFORE ACCUMULATIONS HAVE REACHED ONE THIRD THE DEPTH OF THE BAG. BAGS SHALL BE REPAIRED OR REPLACED AS SOON AS DAMAGE OCCURS.

DETAIL F: CATCH BASIN FILTER BAG (WATER POLLUTION CONTROL)

NOT TO SCALE

DETAIL E: CITY OF STOCKTON SIGNAL POLE CAMERA MOUNTING

NOT TO SCALE

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

DETAILS

DESIGNED UNDER THE SUPERVISION OF: 12/19/2019

DATE

No. 048732 9/30/22

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA DATE: DECEMBER 2019 SCALE: ____

PW1516 SHEET NO. SHEET 5_ OF 36




CHECKED CITY APPROVAL APPROVED BY DAT 1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712


KEYIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

DRAWN BY: MWW


DESIGNED BY: TSW



DETAIL G: TYPE III-AF SERVICE
WIRING DIAGRAM
NOT TO SCALE



DETAIL H: TYPE P CONTROLLER CABINET FOUNDATION NOT TO SCALE



DETAIL I: TYPE P CONTROLLER CABINET FOUNDATION MODIFICATION

NOT TO SCALE

CA: 1-800-227-2600

BEFORE POLICY

CA: 1-800-227-2600

CALL TWO WORKING
DAYS BEFORE YOU DIG


NO. DESCRIPTION CHECKED CITY APPROVAL
APPROVED BY DATE

Kimley >>> Horn

1300 Clay Street Suite 325 © 2019

1300 Clay Street, Suite 325 © 2019 Oakland, California 94612 Phone: (510) 625-0712 DESIGNED UNDER THE SUPERVISION OF:

| 12/19/2019 | KEVIN G. AGUIGUI | DATE | R.C.E. No. 048732, EXP. 9/30/22



DEPARTMENT OF PUBLIC WORKS
CITY OF STOCKTON, CALIFORNIA

DATE: DECEMBER 2019
SCALE: NONE APPROVED BY: DATE: 3/3/20 PV

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

DETAILS

DECEMBER 2019


E: NONE APPROVED BY: DATE: 3 2 2 PROJECT NO.


PW1516
SHEET NO.

DT 4

SHEET 6 OF 36

5365.5C





DETAIL K: ACCESSIBLE PEDESTRIAN SYSTEM FLUTED DECORATIVE POLE MOUNT NOT TO SCALE

DETAIL J: ACCESSIBLE PEDESTRIAN SYSTEM **CUSTOM ADAPTOR PLATE**

NOT TO SCALE



CHECKED CITY APPROVAL
BY APPROVED BY DAT 1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF:

12/19/20 DATE KEVIN G. AGUIGUI

	PROFESSIONAL G. A GUI CHE	
040	NEES/	
019	No. 048732	S
	* 9/30/22 *	C
	OF CALIFORNIA	0
	OF CALIF	C

DETAILS DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA


BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

DATE: DECEMBER 2019 SCALE: NONE DRAWN BY: TSW DESIGNED BY: ISW

CHECKED BY: EKC

5365.6C

R.C.E. No. 048732, EXP. 9/30/22



BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

SYSTEM DIAGRAM

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DATE: DECEMBER 2019 SCALE: NONE DRAWN BY: MWW DESIGNED BY: TSW

No. 048732 9/30/22

CIT ENGINEER STOCKTON, CALIFORNIA

PW1516 SHEET NO.

SY-1

SHEET 8 OF 36

5365.7C

CA: 1-800-227-2600-CALL TWO WORKING DAYS BEFORE YOU DIG


CHECKED CITY APPROVAL
BY APPROVED BY DATE


1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625—0712

12/19/2019 KEMIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22


DESIGNED UNDER THE SUPERVISION OF:

DATE





MONUMENT TABLE								
EASTING	NORTHING	ELEVATION	DESCRIPTION					
2173513.54	6344145.12	23.64	BRASS DISK MARKING COS MONUMENT STAMPED "55-6" IN MONUMENT WELL ON THE WEST SIDE OF FILBERT ST 5 FT SOUTH OF THE SOUTH RAIL OF THE S.P.R.R. TRACK.					
2171010.94	6344920.65	24.11	BRASS DISK MARKING COS MONUMENT STAMPED "5S-7" IN MONUMENT WELL AT THE INTERSECTION OF APPROXIMATE CENTERLINES OF FILBERT ST AND MAIN ST.					
2167317.50	6343741.87 24.97		BRASS DISK MARKING COS MONUMENT STAMPED "55-12" IN MONUMENT WELL IN TRAFFIC CONTROL ISLAND AT THE SOUTH SIDE OF CHARTER WAY AT MARIPOSA RD.					



BASIS OF BEARING

HORIZONTAL DATUM:

NAD83(1991.35), CALIFORNIA COORDINATE SYSTEM ZONE 3, PER THE CITY OF STOCKTON HORIZONTAL CONTROL SYSTEM PHASE XIV PER THE RECORD OF SURVEY ON FILE IN BOOK 35 OF SURVEYS, AT PAGE 5, SAN JOAQUIN COUNTY RECORDS. SEE SAID SURVEY FOR MORE DETAILS.

VERTICAL DATUM:

NAVD88, PER THE 2011 CONVERSION OF THE CITY OF STOCKTON BENCHMARK NETWORK.

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

HORIZONTAL CONTROL PLAN FILBERT STREET AT LAFAYETTE STREET & MAIN STREET AT FIBLERT STREET

DEPARTMENT OF PUBLIC WORKS

CITY OF STOCKTON, CALIFORNIA

		NO.	DESCRIPTION	CHECKED	CITY APPRO	DVAL	
GRAPHIC SCALE	-	-		BY	APPROVED BY	DATE	Kimley»
o 20 40 80	SNS						
	NSIC NSIC	\dashv					1300 Clay Street, Suite 325
(IN FEET)	RE						Oakland, California 94612
1 inch = 40 ft.							Phone: (510) 625-0712

Street, Suite 325 alifornia 94612

R.C.E. No. 048732, EXP. 9/30/22

12/19/2019 DATE KEVIN G. AGUIGUI

DESIGNED UNDER THE SUPERVISION OF:


No. 048732 9/30/2**2**


DATE: DECEMBER 2019 SCALE: AS NOTED DRAWN BY: JTXBL CHECKED BY: EKC DO

PW1516

5365.90

CA: 1-800-227-2600-CALL TWO WORKING DAYS BEFORE YOU DIG







CALL TWO WORKING

DAYS BEFORE YOU DIG

(IN FEET)

1 inch = 5 ft.





LEGEND

SIDEWALK (6" PCC / 4" AB)

DETECTABLE WARNING SURFACE

AC PLUG (8")

∵∷∷ NATIVE

-/-//- SAWCUT ---- GRADEBREAK

CONSTRUCTION NOTES

1 EXISTING TO REMAIN

3 CONFORM TO EXISTING (SEE NOTE 1)

5 EXISTING SIGNAL UTILITY. SEE SIGNAL SHEETS FOR MORE DETAIL

12 CONSTRUCT "CASE B" CURB RAMP PER 2018 CALTRANS STANDARD PLANS A88A

13 CONSTRUCT SIDEWALK PER CITY OF STOCKTON ─ DWG NO. R-50

14 CONSTRUCT CURB AND GUTTER PER CITY OF STOCKTON DWG NO. R-52

19 CONSTRUCT "CASE C" CURB RAMP PER 2018 CALTRANS STANDARD PLANS A88A

GENERAL NOTES

CONFORM SIDEWALK AT SCOREMARK OR NEAREST EXPANSION JOINT. EXACT LIMITS TO BE DETERMINED IN THE FIELD BY ENGINEER OR CONTRACTOR. SIDEWALK CONFORM TO EXISTING SHALL FOLLOW CITY OF STOCKTON DWG NO. R-55, R-56.

ABBREVIATIONS

BEGIN CURVE BACK OF WALK BW CURB & GUTTER C&G CL CENTERLINE DWY DRIVEWAY FH FIRE HYDRANT FLOWLINE GB JP GRADE BREAK JOINT POLE SDCB STORM DRAIN CATCH BASIN SDMH STORM DRAIN MANHOLE SW SIDEWALK TOP OF CURB VG VALLEY GUTTER WATER VALVE

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, REMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

CONSTRUCTION DETAILS

FILBERT STREET AT LAFAYETTE STREET

DEPARTMENT OF PUBLIC WORKS

CITY OF STOCKTON, CALIFORNIA DATE: DECEMBER 2019

CITY ENGINEER SHEET 12 OF 3

PW1516 SHEET NO.

STOCKTON, CALIFORN


SCALE: AS NOTED

DESIGNED UNDER THE SUPERVISION OF: 1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712


KEVÍN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22


12/19/2019 DATE


No. 048732



5365.12C









GENERAL NOTES

- 1. ALL PAVEMENT MARKINGS SHALL BE PER CALTRANS STANDARD PLANS A24A THROUGH A24E.
- 2. ALL STRIPING OR PAVEMENT MARKINGS SHALL BE THERMOPLASTIC.
- 3. REMOVE ALL CONFLICTING LANE LINES OR PAVEMENT MARKINGS.
- 4. ALL STRIPING SHALL BE PER CA MUTCD.

SIGNING AND STRIPING **CONSTRUCTION NOTES**


- 2 INSTALL 24" WHITE ADVANCE LIMIT LINE 7' FROM CROSSWALK STRIPING PER CITY OF STOCKTON DRAWING NO.
- 3 INSTALL DETAIL 22 THERMOPLASTIC CENTERLINE STRIPE. LENGTH AS INDICATED ON PLAN.
- (5) INSTALL WHITE TYPE IV LEFT ARROW PAVEMENT MARKING.
- 6 INSTALL BIKE DETECTOR SYMBOL CENTERED IN LANE AND 1' FROM LIMIT LINE PER CITY OF STOCKTON DRAWING NO.
- 7 INSTALL DETAIL 38 WHITE THERMOPLASTIC LANE LINE. LENGTH AS NOTED ON PLAN.
- 8 REMOVE EXISTING STRIPING OR PAVEMENT MARKING.
- 9 INSTALL 12" WHITE THERMOPLASTIC CROSSWALK LINE AT 10' ON CNTER AT CURB RAMPS.
- 10 INSTALL DETAIL 9 WHITE THERMOPLASTIC LANE LINE. LENGTH AS NOTED ON PLAN.
- INSTALL WHITE TYPE VII RIGHT AND THROUGH ARROW PAVEMENT MARKING.
- 12 INSTALL 4" WHITE THERMOPLASTIC LANE LINE STRIPE WITH WHITE TYPE G MARKERS PER DETAIL 27M. REFER TO SECTION 9-1.02 (DESCRIPTION OF WORK) OF THE SPECIAL PROVISIONS FOR PAYMENT. LENGTH AS NOTED ON PLAN.






CA: 1-800-227-2600-

CALL TWO WORKING DAYS BEFORE YOU DIG



CHECKED CITY APPROVAL
BY APPROVED BY DATE

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712





BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

SIGNING AND STRIPING PLAN MAIN STREET AT FILBERT STREET

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

PROJECT NO. PW1516 SHEET NO. CITY ENGINEER STOCKTON, CALIFORNIA SS-2

SHEET 16 OF 36


CONDOC	JUR	S (CHE	DUL	.E		
,						JCTC	
CONDUCTOR DESIGNATION	WE	BER	AVE	AND	CEN	TER :	ST
	7	121	/3\		公	/6\	1
28-CONDUCTOR CABLES	 ' ' '	/	, , ,	/ + \	, ,	, 0	-
POLE A	1	1				1	H
POLE C	1 1	1	1	1		<u> </u>	H
POLE E	1	1	1				H
FOLE E	+ '						H
TOTAL 28-CONDUCTOR CABLES	3	3	1	1		1	_
12-CONDUCTOR CABLES	+						H
POLE B	1	1	1	1	1		H
	<u> </u>		1	ł	-	4	H
POLE F						1	_
TOTAL 40 CONDUCTOR CARLED	-	4	4	4	4	4	-
TOTAL 12-CONDUCTOR CABLES	1	1	1	1	1	1	_
							L
3-CONDUCTOR CABLES							L
POLE A	1	1				1	L
POLE B	1	1	1	1	1		L
POLE C	1	1	1	1			L
POLE D	1	1					
POLE E	1	1					
POLE F	1	1				1	
TOTAL 3-CONDUCTOR CABLES	6	6	2	2	1	2	F
NO. 10 CONDUCTORS							Г
STREET OUTLETS		3	3	2			Г
							Г
TOTAL NO. 10		3	3	2			
NO. 8 CONDUCTORS	1						┢
SERVICE	3						┢
INTERSECTION LIGHTING	+	.4	3	3	3	3	-
STREET LIGHTING	╅╾	4	4	3	 	Ŭ	H
STREET LIGITING	+		7	<u> </u>			H
TOTAL NO. 8	3	8	7	6	3	3	H
	+ -	0	/	0	<u> </u>	3	H
DETECTOR LEAD-IN CABLES	+						H
Ø2	3						H
ø3	3	3	3	7	7		\vdash
***	13	٦	J	3	3		\vdash
TOTAL DLC	-	-7	7	7	7		-
TOTAL DEC	6	3	3	3	3		-
VIDEO DETECTION	+						\vdash
COAXIAL CABLE	A	A	4	4		4	-
POWER CABLE		4 _R		1 _R		1 _R	
I OWEN CADLE	4 _R	4 _R	1 _R	1 _R		1 _R	
EVP CABLES	+						\vdash
EVA CABLES	1	4					-
	1	1		-4		<u> </u>	H
EVB	1	1	1	1		<u> </u>	L
EVC	 .	_				-	L
EVD	1	1				1	L
	1					ļ	Ŀ
TOTAL EVP CABLES	3	3	1	1		1	L
							L
APS CABLE (4C#18)				2 _N		2 _N	Ĺ
PTZ COMMUNICATION CABLE*	2	2	1	1	1	1	
PERCENT FILL	17	29	17	16	13	22	7
		2-3"		4"	3"	3"	1

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.


N - DENOTES NEW CONDUCTOR OR CONDUIT
R - DENOTES REMOVE UNUSED CONDUCTORS FROM EXISTING CONDUIT
* POWER AND DATA CABLES (PER MANUFACTURER)

CONSTRUCTION NOTES: (THIS SHEET ONLY)

- 1 FURNISH AND INSTALL 2.5" RIGID METAL CONDUIT FOR FIBER OPTIC CABLE INTO NEW FOUNDATION PER DETAIL H, SHEET DT-4.
- REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC ex2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- REMOVE AND SALVAGE EXISTING TYPE M TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. REMOVE AND DISPOSE OF EXISTING FOUNDATION. FURNISH AND INSTALL NEW TYPE P TRAFFIC SIGNAL CONTROLLER CABINET AND FOUNDATION AT LOCATION OF REMOVED CABINET PER DETAIL H, ON SHEET DT-4. TERMINATE ALL WRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED.
- FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- ROUTE EXISTING COAXIAL CABLES, COILED IN PULL BOX, INTO CONTROLLER CABINET AND PROTECT IN PLACE.
- FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM ON FLUTED POLE PER DETAIL K AND DETAIL J ON SHEET DT-5. APS SYSTEM SHALL BE CONNECTED TO THE FLUTED POLE WITHOUT IMPACTING THE DECORATIVE BASE. ADAPTOR PLATE TO BE APPROVED BY ENGINEER PRIOR TO INSTALLATION.
- 51 FURNISH AND INSTALL TWO (2) ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEMS ON FLUTED POLE PER DETAIL K AND DETAIL J ON SHEET DT-5. APS SYSTEMS SHALL BE CONNECTED TO THE FLUTED POLE WITHOUT IMPACTING THE DECORATIVE BASE. ADAPTOR PLATE TO BE APPROVED BY ENGINEER PRIOR TO INSTALLATION.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.








EXISTING PHASE DIAGRAM (TO REMAIN)

EVP ASSIGNMENTS

 $EVA = \emptyset2$ $EVB = \emptyset4$

 $EVD = \emptyset 8 + \emptyset 3$



WEBER AVENUE

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDOR

TRAFFIC SIGNAL MODIFICATION

WEBER AVENUE AT CENTER STREET

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DATE: DECEMBER 2019 SCALE: AS NOTED


PW1516 SHEET NO. DESIGNED BY: TSW

CHECKED BY: EKC

CITY ENGINEER

STOCKTON, CALIFORNIA

DETAIL	"A"
SCALF: 1" =	5'



KEXIN G. AGUIGUI R.C.E. No. '048732, EXP. 9/30/22

DESIGNED UNDER THE SUPERVISION OF:

EX. PTZ CAMERA ·

EX. 2.5" c,

EX. 2" c, PG&E service

52 50

2 coaxial

EX. 2"c

SEE DETAIL "A", THIS SHEET

cables

EX. 2.5" c,-2 coaxial

cables

EX. 2" c,

PG&E service

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712

No. 048732

CALL TWO WORKING DAYS BEFORE YOU DIG

CA: 1-800-227-2600-

12/19/2019

DATE

5365.16C

SHEET 17 OF 36

			CHE	שטנ	_E							
CONDUCTOR DESIGNATION	<u> </u>					OF CONDUCTORS AND EL DORADO ST						
		/2\		<u>冷</u>					/ ₉ \			
28-CONDUCTOR CABLES												
POLE A	1					1	1	1		1		
POLE C	1					1	1			Γ		
POLE E	1		1							Г		
POLE H	1			1	1					Г		
										Γ		
TOTAL 28-CONDUCTOR CABLES	4		1	1	1	2	2	1				
12-CONDUCTOR CABLES									<u> </u>	H		
POLE B										H		
POLE D							1			\vdash		
POLE F		1	1				'		-	┝		
	+		1	-	1					\vdash		
POLE G	+									\vdash		
TOTAL 40 CONDUCTOR CARLES				-	4		4		\vdash	\vdash		
TOTAL 12-CONDUCTOR CABLES	-	1	1_		1_		1		_	Ľ		
7. 0010110700 010170		_								1		
3-CONDUCTOR CABLES	+_							_		1		
POLE B	1 _N	_					1 _N			\vdash		
POLE C	1 _N					1 _N				L		
POLE D	1 _N					1 _N				L		
POLE F	1 _N	1 _N			·					L		
POLE G	1 _N			1 _N								
POLE H	1 _N			1 _N	1 _N					Г		
POLE 1	1 _N					1 _N	1 _N	1 _N		Ŀ		
POLE J	1 _N		1 _N									
TOTAL 3-CONDUCTOR CABLES	8 _N	1 _N	1 _N	2 _N	1 _N	4 _N	3 _N	2 _N				
NO. 8 CONDUCTORS		_								╁		
SERVICE	2									T		
STREET LIGHTING	+-	2	5	2	2	8	2	2				
JIKEET CIGITING	+-	<u> </u>	<u> </u>		_	Ť	_	_		╁		
TOTAL NO. 8	2	2	5	2	2	8	2	2				
DETECTOR LEAD-IN CABLES										F		
Ø2	4								4	T		
ø3	2								-	+		
	14								 	\vdash		
TOTAL DLC	6									\vdash		
· · · · · · · · · · · · · · · · · · ·	10									\vdash		
EVP CABLES	+									\vdash		
EVA	+-					4	4	<u> </u>		\vdash		
EVB	1 _N						1 _N			Η.		
EVD	1 _N		-			L N	1 _N	IN		<u> </u>		
LVU	1 _N		1 _N	_						\vdash		
TOTAL EVP CABLES	3 _N		1 _N			2 _N	2 _N	1 _N				
ADC CADIF (40/40)			_		_				_	<u> </u>		
APS CABLE (4C#18)			2 _N		2 _N		2 _N			1		
PTZ COMMUNICATION CABLE*	$1,2_{R}$					$1,2_R$	$1,2_R$	$ 1,1_{R} $		L		
DEDOGNIT SILL					. =				_	\vdash		
PERCENT FILL	1.30	18	146	14	17	34	1.33	17	8	2		
CONDUIT SIZE	2-3"		2"	3"	3"	3"	3"	3"	2"	3		

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS


OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR OR CONDUIT

R - DENOTES REMOVE UNUSED CONDUCTORS FROM EXISTING CONDUIT * POWER AND DATA CABLES (PER MANUFACTURER)

CONSTRUCTION NOTES: (THIS SHEET ONLY)

- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- 3 INSTALL CITY-FURNISHED OPTICOM MODEL 768 AUXILIARY PANEL IN TRAFFIC SIGNAL CONTROLLER CABINET.
- REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER
- FURNISH AND INSTALL NEW PEDESTRIAN PUSH BUTTON POST WITH ONE ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- REMOVE AND SALVAGE EXISTING EVP DETECTOR UNIT TO CORPORATION YARD. FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON EXISTING MOUNTING. FURNISH AND INSTALL EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN.
- FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM ON FLUTED POLE PER DETAIL K AND DETAIL J ON SHEET DT-5. APS SYSTEM SHALL BE CONNECTED TO THE FLUTED POLE WITHOUT IMPACTING THE DECORATIVE BASE. ADAPTOR PLATE TO BE APPROVED BY ENGINEER PRIOR TO INSTALLATION.
- 53 FURNISH AND INSTALL NEW PUSH BUTTON CONDUCTORS BETWEEN ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) AND CABINET. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.
- 54 REPOUTE EXISTING CONDUCTORS IN NEW CONDUIT PER CONDUCTOR SCHEDULE.
- 55 RELEVEL EXISTING PAVERS AROUND THE PULL BOX.



EXISTING PHASE DIAGRAM (TO REMAIN)


EVP ASSIGNMENTS

 $EVA = \emptyset2$ $EVB = \emptyset4$

 $EVD = \emptyset 8 + \emptyset 3$


POLE	TYPE	LOCATION				
POLE	I I I E	A	В			
	PPB POST	-1.6'	4.3'			
(-)	PPB POST	1.6'	1.8'			

SIGNAL STANDARD PLACEMENT DIMENSIONS (CALTRANS STANDARD PLAN ES-4C)




BEFORE YOU	
[] [] [] [] [] [] [] [] [] []	
US	
GIJORO SERVICE ME	
CA: 1-800-227-2600	,

DAYS BEFORE YOU DIG



1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712



KEVIN G. AGUIGUI

R.C.E. No. 048732, EXP. 9/30/22

12/19/2019

DATE

No. 048732 9/30/22


TRAFFIC SIGNAL MODIFICATION WEBER AVENUE AT EL DORADO STREET

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

DESIGNED BY: TSW CHECKED BY: EKC

5365.17C



GRAPHIC SCALE (IN FEET) 1 inch = 20 ft.

DATE: DECEMBER 2019

CITY ENGINEER STOCKTON, CALIFORNIA

PROJECT NO. PW1516 SHEET NO.

SHEET 18 OF 36

CA: 1-800-227-2600 CALL TWO WORKING

- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 13 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON PEDESTRIAN SIGNAL HEAD. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PLASE AS INDICATED ON PLAN SEE DETAIL A ON SHEET DE 1 FOR MOUNTING DETAILS PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET, CONTRACTOR TO REINSTALL FIBER OPTIC ' CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 21 FURNISH AND INSTALL NEW PEDESTRIAN PUSH BUTTON POST WITH ONE ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- REMOVE AND SALVAGE EXISTING TYPE M TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. FURNISH AND INSTALL NEW TYPE M (TALL) TRAFFIC SIGNAL CONTROLLER CABINET ON EXISTING FOUNDATION. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED. VERIFY THE LOCATION OF ALL EXISTING FIBER OPTIC CABLE AND PROTECT IN PLACE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 41 FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.
- 53 FURNISH AND INSTALL NEW PUSH BUTTON CONDUCTORS BETWEEN ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) AND CABINET. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS
- 57 INSTALL No. 5 TRAFFIC RATED PULL BOX IN EXISTING CONDUIT RUN.
- 62 PULL CONDUCTORS IN CONDUIT (8) BACK TO HOMERUN PULL BOX. REINSTALL CONDUCTORS AFTER INSTALLATION OF NEW PULL BOX.

CONDUCTOR	SCHE	DUL	E.									
	NUMBER OF CONDUCTORS											
CONDUCTOR DESIGNATION	WEE	WEBER AVE AT SAN JOAQUIN ST										
		/2\	/3\	/4\	/ <u>5</u> \	/6\	/2\	/8\	%			
NO. 14 CONDUCTORS	- ()	125	, ,	4	73	00	/ / \	0	791			
SIGNALS	15	12	9	9	6	6	3	3				
PED	12	8	6	6	6	4	2	4				
ø2 PPB		2 _N			_	<u> </u>		-				
Ø4 PPB	2 N	1 N	1 N	1 N	1 N	1 N		1 _N	1 ,			
ø6 PPB	1, 1 N		·N	·N		. N		1 1				
Ø8 PPB		2 _N	1	1 ,,								
SPARE	6	3	3	N	3	3	3	3				
PEU	2			<u> </u>				<u> </u>				
												
TOTAL NO. 14	36, 7 _N	23. 5.	18.4	18.4	15.3	13.2	8	11, 1 _N	1 ,			
			, . ,						_ · N			
NO. 10 CONDUCTORS												
SIGNAL COMMON	1	1	1	1	1	1	1	1				
TOTAL NO. 10	1	1	1	1	1	1	1	1				
NO. 8 CONDUCTORS												
STREET LIGHTING			4	4	4	4	4					
SERVICE	2	2										
									-			
TOTAL NO. 8	2	2	4	4	4	4	4					
DETECTOR LEAD-IN CABLE												
							-					
APS CABLE (4C#18)		2 _N	-		2 _N		2 _N		1 _N			
PTZ VIDEO CABLE	1	1										
GPS COMMUNICATION CABLE	1											
FIBER OPTIC CABLE	1											
EVP CABLES**												
EVA	1 _N	1 _N	1 _N	1 _N	1 _N	1 _N	1 _N					
EVB	1 _N											
EVC	1 _N	1 _N										
EVD	1 N		1 _N	1 _N	1 _N							
TOTAL EVP CABLES	4 N	3 _N	2 _N	2 _N	2 _N	1 _N	1 _N					
PERCENT FILL	12		17					15				
CONDUIT SIZE	2-3"	3"	2.5"	2.5"	2.5"	2.5"	1.5"	1.5"	1.5			

STEADY DEMAND SEQUENCE ø2


EXISTING PHASE DIAGRAM (TO REMAIN)

EVP ASSIGNMENTS


 $EVA = \emptyset2$

 $EVB = \emptyset4$


 $EVC = \emptyset6$ $EVD = \emptyset 8$



SIGNAL STANDARD PLACEMENT DIMENSIONS (CALTRANS STANDARD PLAN ES-4C)



LOCATION POLE 3.7' PPB POST -3.8'-1.2'2.2' PPB POST



BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDOR;

TRAFFIC SIGNAL MODIFICATION

DATE: DECEMBER 2019 SCALE: AS NOTED CHECKED BY: EKC

WEBER AVENUE AT SAN JOAQUIN STREET

	DEPA	RTN	1ENT	OF	PUI	BLIC	WORK	(S
	CITY	OF	STO	CKT	ON,	CALI	FORN	IA
חדם	2010							

PROJECT NO. PW1516 SHEET NO. SHEET 19 OF 3

-CA: 1-800-227-2600-

CALL TWO WORKING

DAYS BEFORE YOU DIG

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.

- N DENOTES NEW CONDUCTOR OR CONDUIT
- * POWER AND DATA CABLES (PER MANUFACTURER) ** OPTICOM GTT MODEL 138 CABLE

	Н	NO.	DESCRIPTION	CHECKED	CITY APPRO	OVAL
				BY	APPROVED BY	DATE
			; 			
	SS		: 			
	SIONS				,	
-	æ					

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712

KEVIN G. AGUIGUI

R.C.E. No. 048732, EXP. 9/30/22

DESIGNED UNDER THE SUPERVISION OF:

12/19/2019 DATE

No. 048732 9/30/22

STOCKTON, CALIFORNIA

21 FURNISH AND INSTALL NEW PEDESTRIAN PUSH BUTTON POST WITH ONE ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.

41 FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.

52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER

57 INSTALL No. 5 TRAFFIC RATED PULL BOX IN EXISTING CONDUIT RUN.

FURNISH AND INSTALL NEW PUSH BUTTON CONDUCTORS BETWEEN ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM AND NEAREST PULL BOX.
FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE

[63] PULL CONDUCTORS IN CONDUIT 2 BACK TO PULL BOX IN MEDIAN. REINSTALL CONDUCTORS AFTER INSTALLATION OF NEW PULL BOX.

65 CONNECT NEW PUSH BUTTON CONDUCTORS FOR PUSH BUTTON POST TO EXISTING PUSH BUTTON CONDUCTORS IN THE PULL BOX.


		<u> </u>									
CONDUC	TOR S	CHE	EDU	LE					ŧ		
	NUMBER OF CONDUCTORS										
CONDUCTOR DESIGNATION WEBER AVE AT SUTTER S							ST				
	介	/2\	/3\	/4\	/ ₅ \	/6\	/ / /	/8 \	/ <u>\$</u> \	10	/11
NO. 14 CONDUCTORS											
SIGNALS	15	15	9	9	3	3	3		6	6	3
PED	12	12	8	6	6	4	4		4	4	2
PPB	4	4	2	2	2	2	2	2 _N	2	2	2
SPARE	6	6	3	3	3	3 _N	3		3	3	3
PEU	2	2									
TOTAL NO. 14	39	39	22	20	14	9, 3 _N	12	2	15	15	10
TOTAL NO. 14	- 33	33		20	17	J , C	12	2- N	10	13	10
NO. 10 CONDUCTORS						- 1					
ROADWAY LIGHTING		<u> </u>	2	2	2	2		_	2	2	2
TOTAL NO. 10			2	2	2	2			2	2	2
NO. 8 CONDUCTORS											
SERVICE	2	2	2	2							
SIGNAL COMMON	1	1	1	1	1	1	1		1	1	1
TOTAL NO. 8	3	3	3	3	1	1	1		1	1	1
DETECTOR LEAD-IN CABLE											
APS CABLE (4C#18)			2 _N		2 _N			1 _N			2
PTZ VIDEO CABLE	1	1	,					<u> </u>	1	1	1
GPS COMMUNICATION CABLE	1	1			l						
FIBER OPTIC CABLE											
EVP CABLES**					<u> </u>						<u> </u>
EVA CABLES***	1	1	1	1	1	1			 		
EVB	1	1	1	1	├-	 			\vdash	\vdash	\vdash
EVC	1	1		 ' -	\vdash			 	 		\vdash
EVD	1	1							1	1	1
TOTAL EVP CABLES	4	4	2	2	1	1			1	1	1
PERCENT FILL	16	32	18	16	11	9	10	4	1.3	13	12
CONDUIT SIZE	2-2.5	2 5"	2 5"	2 5"	2 5"	2 5"	2"	1.5"	2 5"	5 5"	7 5

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS

OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR OR CONDUIT * POWER AND DATA CABLES (PER MANUFACTURER)

** OPTICOM GTT MODEL 138 CABLE




EXISTING PHASE DIAGRAM (TO REMAIN)

EVP ASSIGNMENTS


 $EVA = \emptyset2$


 $EVB = \emptyset 4$ $EVC = \emptyset 6$

 $EVD = \emptyset 8$




SIGNAL STANDARD PLACEMENT DIMENSIONS (CALTRANS STANDARD PLAN ES-4C)





POLE	TYPE	LOCATION					
POLL	11114	A	В				
H	PPB POST	-4.9'	3.5'				
	PPB POST	5.7'	3.6'				



PROJECT NO. PW1516 SHEET NO.

SHEET 20 OF 36

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDOR

TRAFFIC SIGNAL MODIFICATION WEBER AVENUE AT SUTTER STREET

> DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DATIE: DECEMBER 2019 DESIGNED BY: TSW

CHECKED BY: EKC

CHECK



N	10.	DESCRIPTION	CHECKED	CITY APPRO	DVAL	
			BY	APPROVED BY	DATE	
	Т					
18						
SION						
Ä	\neg					
	\dashv					ı
	十					
	\dashv					ı

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712


12/19/2019 KEVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

DESIGNED UNDER THE SUPERVISION OF:

DATE

No. 048732 9/30/2²

5365.190



- 3 INSTALL CITY-FURNISHED OPTICOM MODEL 768 AUXILIARY PANEL IN TRAFFIC SIGNAL CONTROLLER CABINET.
- FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- 28 REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING WIRING.
- 29 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- REMOVE EXISTING AUDIBLE PEDESTRIAN SIGNAL FROM PEDESTRIAN SIGNAL HEAD. AUDIBLE PEDESTRIAN SIGNAL TO BECOME PROPERTY OF CONTRACTOR. SEAL HOLE IN PEDESTRIAN SIGNAL HEAD WITH WATERTIGHT GROMMET.
- REMOVE AND SALVAGE EXISTING PTZ CAMERA AND POWER CABLE. FURNISH AND INSTALL NEW IP PTZ CAMERA ON SIGNAL POLE. SEE DETAIL C, ON SHEET DT-2, FOR MOUNTING DETAILS. FURNISH AND INSTALL NEW CATS CABLE TO TRAFFIC SIGNAL CABINET.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.


CONDUCTOR	R S(CHE	DUL	E.					
		NUI	MBE	₹ 01	F CC	DND	JCTO	DRS	
CONDUCTOR DESIGNATION	N	IINE	R A'	VE A	AT A	IRP	ORT	WA.	Y
	<u> </u>	/2\	/3\	/ <u>4\</u>	/5\	/6\	/2\	/8\	/ ₉ \
NO. 14 CONDUCTORS									
SIGNALS	24	24	21	21	15	15	9	9	3
PED	8	8	8	8	8	6	6	4	2
PPB	4	4	4	4	3	3	2	2	1
PEU		3							
SPARE	3	3	3	3	3	3	3	3	3
TOTAL NO. 14	39	42	36	36	29	27	20	18	9
NO. 12 CONDUCTORS									
PPB COMMON	1	.1	1	1	1	1	1	1	1
TOTAL NO. 12	1	1	1	1	1	1	1	1	1
NO. 8 CONDUCTORS									
SERVICE	3								
LUMINAIRE		2	2	2	2	2	2	2	
SIGNAL COMMON	1	1	1	1	1	1	1	1	1
TOTAL NO. 8	4	3	3	3	3	3	3	3	1
DETECTOR LEAD-IN CABLE	15	15	15	13	11	7	7	5	3
PTZ VIDEO CABLE	1 _R ,1 _N	1 _R ,1 _N	1 _R ,1 _N	$1_R,1_N$	1 _R ,1 _N	1 _R ,1 _N	1 _R ,1 _N	$1_R,1_N$	
GPS COMMUNICATION CABLE	1	1		,,,,,,					
FIBER OPTIC CABLE	1								
EVP CABLES									
EVA	1	1	1	1					
EVB	1	1							
EVC	1	1	1	1	1	1	1	1	
EVD	1	1	1	1	1	1			
						_			
TOTAL EVP CABLES	4	4	3	3	2	2	1	1	
APS CABLE (4C#18)			2 _N		2 _N		2 _N		2 _N
PERCENT FILL	11	19	16	19	25		26		30
CONDUIT SIZE	2-4°	4"	2-3"	3"	3"	2.5	2.5"	2"	1.5"


EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS

OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR

R - DENOTES REMOVE UNUSED CONDUCTORS FROM EXISTING CONDUIT





 $EVC = \emptyset6 + \emptyset1$

EXISTING PHASE DIAGRAM (TO REMAIN)

EVP ASSIGNMENTS

STEADY DEMAND SEQUENCE

 $EVB = \emptyset 4 + \emptyset 7$

52 29 28 EX. SJRTD EX. 2"c, f.o. CABLE EX. SJRTD BUS STOP E MINER AVE 52 29 28



CHECKED CITY APPROVAL
BY APPROVED BY DATE

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF:

KEVIN G. AGUIGUI

R.C.E. No. 048732, EXP. 9/30/22

12/19/2019

DATE

No. 048732 9/30/22

MINER AVENUE AT AIRPORT WAY DEPARTMENT OF PUBLIC WORKS

GRAPHIC SCALE

(IN FEET) 1 inch = 20 ft.

PW1516 SHEET NO.

TS-6

CITY OF STOCKTON, CALIFORNIA

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS


TRAFFIC SIGNAL MODIFICATION

CITY ENGINEER
STOCKTON, CALEORNI SHEET 22 OF 36

- REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- REMOVE AND DISPOSE OF EXISTING TYPE III SERVICE CABINET. INSTALL NEW TYPE III SERVICE CABINET ON EXISTING FOUNDATION. CONTACT CITY MAINTENANCE FOR DISCONNECT AND RECONNECT.
- 17 REMOVE EXISTING 8" SIGNAL HEADS AND TV-2-T MOUNTING FRAME. SIGNAL HEADS TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW TV-2-T MOUNTING FRAME. CONNECT NEW SIGNAL HEADS TO EXISTING WIRING.
- 28 REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING
- 29 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS

3 6 6 3 3 3 3 4	3 3 3	MII 3 3			OF OF				AY	——	
6 6 3 3 3 3 3	3 3 3	3 3	4	X		/}\				$\overline{\Lambda}$	
6 6 3 3 3 3 3	3	3	3					/ J V	NΟN	/11\	12
6 6 3 3 3 3 3	3	3	3								
6 3 3 3 3	3				3						
3 3 3 3			3		6	3	7				
3 3 3 3		3	3	3	6 3	3	3				
3 3 3					3	3	٥			\vdash	
3 3	3	3			3						
3	3				3						
	3	3	3	3	3						
1 +	2	2	2		4	2					
4					4	2	2				
2	1				2						
2	2	2	2	2	2						
2	1	1	1	1	2	1	1				
2	<u> </u>				2	1					
2	1		_		2						
2	2	2	1	4	2		1	-	\vdash		
2 6	3	3	3	3	6	3	3				
0	3	٦		٦	0	٦	5				
60	32	28	22	13	63	22	13				
	2	2	2	2	2	2	2				
	1	1	1	1	1	1	1				
	3	3	3	3	3	3	3				
		J	J				<u> </u>				
1					1						
			1	1	1						
	-	\vdash			1	1	4				
-	1	1	1	1		<u> </u>	<u> </u>				
	 '	-'-	'	<u> </u>	\vdash						
						1	1				
2	2				2						
9	3	2	2	2	8	2	2				
1	 - 				1			1		 	
	\vdash							•			
1	\vdash								1	1	
1					1		1	1			1
4					2		1	2	1	1	1
							•				
1					1	1					
-	-	4									
			4	4							
-									\vdash		
 				2	2		2			2	
				. ~ ~	, ar. =*	, '	. ∠.N	,		<u> </u>	
l 1				N	N		,				
1				N	1						
1								2		2	1
	1 1 1 1 2 9	1	1	1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1	1 1	1 1	1 1	1 1	1

STEADY DEMAND SEQUENCE




EXISTING PHASE DIAGRAM (TO REMAIN)


EVP ASSIGNMENTS

 $EVA = \emptyset 2 + \emptyset 5$

 $EVB = \emptyset 4 + \emptyset 7$

 $EVC = \emptyset6 + \emptyset1$ $EVD = \emptyset8 + \emptyset3$





BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

TRAFFIC SIGNAL MODIFICATION MINER AVENUE AT WILSON WAY

DEPARTMENT OF PUBLIC WORKS

CITY OF STOCKTON, CALIFORNIA

PROJECT NO. PW1516 SHEET NO. SCALE: AS NOTED APPROVED BY DESIGNED BY: TSW

CHECKED BY: EKC

CIPT ENGINEER

STOCKTON, CALIFORNIA


5365.22C

-CA: 1-800-227-2600
BEFORE YOU
2
SÃ T
BERNCE REPORTED TO SERVICE
ACROUND SERVICE
CA: 1-800-227-2600
CALL TWO WORKING

DAYS BEFORE YOU DIG

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR* POWER AND DATA CABLES (PER MANUFACTURER)



1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF:

DATE KEVIN G. AGUIGUI

12/19/2019 No. 048732 9/30/22

R.C.E. No. 048732, EXP. 9/30/22

- 3 INSTALL CITY-FURNISHED OPTICOM MODEL 768 AUXILIARY PANEL IN TRAFFIC SIGNAL CONTROLLER CABINET.
- REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- 6 REMOVE AND SLAVAGE EXISTING PUSH BUTTON POST. FURNISH AND INSTALL 4" DIAMETER PEDESTRIAN PUSH BUTTON POST ON EXISTING FOUNDATION WITH TWO (2) ACCESSIBLE PEDESTRIAN SIGNAL SYSTEMS.
- REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING
- 29 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- REMOVE EXISTING AUDIBLE PEDESTRIAN SIGNAL FROM PEDESTRIAN SIGNAL HEAD. AUDIBLE PEDESTRIAN SIGNAL TO BECOME PROPERTY OF CONTRACTOR. SEAL HOLE IN PEDESTRIAN SIGNAL HEAD WITH WATERTIGHT GROMMET.
- CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.

CONDUCTOR DESIGNATION	·			-			STRE	
	<u>""</u>	/2\	<u>"</u>	<u> </u>	/5\	/6\	小	T /
NO. 14 CONDUCTORS	- ' '	/ 2 \	V 3 \	V 4 \	75	70.	V / \	/8\
Ø1 SIGNALS	3	3	6	3				6
Ø2 SIGNALS		3	3					3
ø3 SIGNALS								
Ø4 SIGNALS	3	3	6	3	3	3	3	6
ø5 SIGNALS		3	3					3
Ø6 SIGNALS			3	3				3
ø7 SIGNALS								
Ø8 SIGNALS			3					3
ø2P PED	2	2						2
ø4P PED	2	2	2	2	2	2	2	2
Ø6P PED			2	2				2
Ø8P PED								
Ø2P PPB	1	1	1			1	1	1
ø4P PPB	1	1	2	1				2
Ø6P PPB			1	1	1			1
Ø8P PPB								
PPB NEUTRAL	1	1	1	1	1	1	1	1
SPARES	3	3	6	3	3	3	3	6
TOTAL NO. 14	16	22	39	10	10		10	70
TOTAL NO. 14	110	22	39	19	10	9	10	39
NO. 10 CONDUCTORS								
STREET LIGHTING	2	<u> </u>		2		2		
SIGNAL NEUTRAL	1	1	1	1	1	1	1_	1
TOTAL NO. 10	3	1	3	3	1	3	1	3
NO. 8 CONDUCTORS								
STREET LIGHTING		2	2					2
								_
TOTAL NO. 8		2	2					2
DETECTOR LEAD-IN CABLE								
Ø2 SAMPLER		2	2					2
ø6 SAMPLER			2	2				2
TOTAL DIO		_	1					
TOTAL DLC	2	6	12	4	2		2	12
INSYNC CAMERA CABLES***								
INSYNC ø2, ø5		1	1					1
INSYNC Ø4, Ø7	1	1	1					1
INSYNC ø6, ø1			1	1				1
INSYNC Ø8, Ø3								1
APS CABLE (4C#18)			1.		2.	2.	2	
EVP CABLES**	1	.2	1 _N		<u> </u>		2 _N	
FIBER OPTIC CABLE	1-1-	2	3	1		_1_	 	4
PTZ VIDEO CABLE*			4	4				1
FIZ VIDEO CADLET			1	1_				1_
PERCENT FILL	16	21			9	13	10	22
CONDUIT SIZE		3"				- 10	2.5"	

STEADY DEMAND SEQUENCE ø4 ø8

EXISTING PHASE DIAGRAM (TO REMAIN)

EVP ASSIGNMENTS

POLE SCHEDULE

OR AS DIRECTED

BY THE ENGINEER

 $EVA = \emptyset2 + \emptyset5$ $EVB = \emptyset4 + \emptyset7$


 $EVC = \emptyset6 + \emptyset1$ $EVD = \emptyset 8 + \emptyset 3$


> CURB/BERM FLOW LINE OR ÉDGE OF SHOULER-FOR "A" AND "B" DIMENSIONS, SEE

SIGNAL STANDARD PLACEMENT DIMENSIONS (CALTRANS STANDARD PLAN ES-4C)

BEGIN CURB

RETURN






f.o. CABLE

52 29 28

EX. PTZ CAMERA -



SHEET 24 OF 36

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDOR

FREMONT STREET

TRAFFIC SIGNAL MODIFICATION

FREMONT STREET AT WILSON WAY

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

STOCKTON, CALIFORNIA

DATE: DECEMBER 2019 PW1516 SHEET NO. SCALE: AS NOTED

5365.23C


2600-
2000
0
% '\
71
2600 -
ING DIG

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.

- N DENOTES NEW CONDUCTOR
- * POWER CABLE (4#14) (BICC TYPE TC600V), BELDON 8281 VIDEO COAXIAL CABLE, DATA CONTROL CABLE (3#16)
- ** OPTICOM GTT MODEL 138 CABLE *** 3#14 (IP CAMERA POWER), 1—CAT5E (IP CAMERA COMM)

ll	NO.	DESCRIPTION	CHECKED	CITY_APPR(OVAL
l			BY	APPROVED BY	DATE
		,			
/ISIONS					
응					
R					

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625—0712



No. 048732 9/30/22

R.C.E. No. 048732, EXP. 9/30/22


EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR * POWER AND DATA CABLES (PER MANUFACTURER)

CONSTRUCTION NOTES: (THIS SHEET ONLY)

- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- 4 REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- 8 FURNISH AND INSTALL IP PTZ CAMERA ON SIGNAL POLE. SEE DETAIL C, ON SHEET DT-2, FOR MOUNTING DETAILS.
- 11 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- 31 FURNISH AND INSTALL 3—SECTION SIGNAL HEAD COVER ON SIGNAL HEAD. SEE SPECIAL PROVISIONS FOR FURTHER DETAIL.
- 33 REMOVE EXISTING 8" SIGNAL HEADS AND SV-2-TB MOUNTING FRAME. SIGNAL HEADS TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL TWO NEW 12" 3-SECTION SIGNAL HEADS ON NEW SV-2-TB MOUNTING FRAME. CONNECT NEW SIGNAL HEADS TO EXISTING WIRING.
- 36 ROUTE EXISTING COAXIAL CABLES, COILED IN PULL BOX, INTO CONTROLLER CABINET AND PROTECT IN PLACE.
- REMOVE AND SALVAGE EXISTING TYPE R TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. REMOVE AND DISPOSE OF EXISTING FOUNDATION FURNISH AND INSTALL NEW TYPE B TRAFFIC SIGNAL CONTROLLER CARINET AND DISPOSE OF EXISTING FOUNDATION. FURNISH AND INSTALL NEW TYPE P TRAFFIC SIGNAL CONTROLLER CABINET AND FOUNDATION AT LOCATION OF REMOVED CABINET PER DETAIL H, ON SHEET DT-4. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED.

STEADY DEMAND SEQUENCE



* FUTURE PHASE

EXISTING PHASE DIAGRAM (TO REMAIN)

EVP ASSIGNMENTS


 $EVA = \emptyset 2 + \emptyset 5$

 $EVB = \emptyset4$ $EVC = \emptyset6 + \emptyset1$


 $EVD = \emptyset8$

48 24 4 2 EX. 2.5"c, 4 coaxial cables— EX. f.o.cable EX. 2.5"c, -EX. 2"c, 3#6, 2 coaxial 1#6(grd) cables

> **DETAIL "A"** SCALE: 1" = 5'



CA. 1-000-221-2000	
BEFORE FOL	
A DO	
GILDERGROUND SERVICE HE	
TOTAL STEERS	
POUND SERVIO	
CA: 1-800-227-2600	



DESIGNED UNDER THE SUPERVISION OF: 12/19/2019

R.C.E. No. 048732, EXP. 9/30/22

r−EX. 2"c,

1#6(grd)

No. 048732

√8,7

Ø2 ·

FREMONT STREET AT EASTLAND DRIVE DATE: DECEMBER 2019 SCALE: AS NOTED DRAWN BY: GMS

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

TRAFFIC SIGNAL MODIFICATION

GRAPHIC SCALE

(IN FEET)

1 inch = 20 ft.

PROJECT NO.

PW1516 SHEET NO.

SHEET 25 OF 36

DESIGNED BY: TSW CHECKED BY: EKC STOCKTON, CALIFORNIA

CA: 1-800-227-2600
BEFORE YOU
3
S S
GING ON SERVICE REPORTED IN THE PROPERTY OF TH
CA: 1-800-227-2600
CALL TWO WORKING DAYS BEFORE YOU DIG

SEE DETAIL "A", THIS SHEET-

EX. 2.5"c, 2 coaxial cables

FREMONT STREET

EX. 2.5"c, 2 coaxial cables-

EX. 2"c, 3#6

1#6(grd)

EX. SJRTD BUS STOP

DATE KEVIN G. AGUIGUI

5345.24C

EX. SJRTD BUS STOP

8 33


- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- 4 REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- 8 FURNISH AND INSTALL IP PTZ CAMERA ON SIGNAL POLE. SEE DETAIL C, ON SHEET DT-2, FOR MOUNTING DETAILS.
- 9 REMOVE AND SALVAGE EXISTING TYPE P TS1 TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. FURNISH AND INSTALL NEW TYPE P TS2 TRAFFIC SIGNAL CONTROLLER CABINET ON EXISTING FOUNDATION. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED.
- 11 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL FRAME. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 14 REMOVE AND DISPOSE OF EXISTING PULL BOX. FURNISH AND INSTALL No. 5 PULL BOX.
- 16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).

- 24 FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING WIRING.
- REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL
- REMOVE EXISTING 8" SIGNAL HEADS AND SV-2-TB MOUNTING FRAME. SIGNAL HEADS TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL TWO NEW 12" 3-SECTION SIGNAL HEADS ON NEW SV-2-TB MOUNTING FRAME. CONNECT NEW SIGNAL HEADS TO EXISTING WIRING.
- REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTONS. FURNISH AND INSTALL TWO (2) ACCESSIBLE PEDESTRIAN SIGNAL SYSTEMS.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.

Ī				E.			
	NU	MBEI	R OI	= C(DND	JCT(ORS
CONDUCTOR DESIGNATION		REM					ST
	1/1	/2\ /2\	/3\	/4\	/ <u>\$</u> \	/6\	
NO. 14 CONDUCTORS							
01	6	3	3	3	3	3	
Ø2 Ø4	3	3	3	3			
Ø6	3	3	3	3			
Ø2P	4	2)	<u> </u>	2	2	
ø4P	2	2	2				
ø2 PPB	2	1			1	1	
Ø4 PPB	2	1	1		1	1	
SPARES	6	3	3	3	3	3	
PEU		3					
TOTAL NO. 14	31	24	18	12	10	10	
NO 10 CONDUCTORS							
NO. 10 CONDUCTORS SIGNAL COMMON	<u> </u>	4	4	4	4		
SIGNAL COMMON	2	1	1	1	1	1	
TOTAL NO. 10	2	1	1	1	1	1	
NO. 8 CONDUCTORS							
SERVICE	3						
LIGHTING (240V)		2	2	2	2		
TOTAL NO. 8	3	2	2	2	2		
DETECTOR LEAD-IN CABLES							
Ø1	2	2	2				
ø2	3	2			1	1	
Ø4	1						
Ø6	3	3	3	2			
TOTAL DLC	9	7	5	2	1	1	
			_				
EVP CABLES							
EVA EVB	1 _N			4			
EVC	1 _N			1 _N			
	'N	_ ' N	I N	ıŅ			
TOTAL EVP CABLES	3 _N	3 _N	2 _N	2 _N			
APS CABLE (4C#18)							$\vdash \vdash \vdash$
FIBER OPTIC CABLE	1	1					
PTZ COMMUNICATION CABLE*	1 _N	1 _N	1 _N	1 _N			
PHONE CABLE	1	1					
PERCENT FILL	16	27	17	26	6	10	
CONDUIT SIZE	2-3"		3"	2"	3"	2"	

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.


N - DENOTES NEW CONDUCTOR* POWER AND DATA CABLES (PER MANUFACTURER)




EXISTING PHASE DIAGRAM

EVP ASSIGNMENTS

 $EVA = \emptyset2$ $EVB = \emptyset4$ $EVC = \emptyset6 + \emptyset1$





Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF:

KEVIN G. AGUIGUI

12/19/2019 DATE R.C.E. No. 048732, EXP. 9/30/22

No. 048732 9/30/22

FREMONT STREET AT E STREET DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA DATE: DECEMBER 2019

SCALE: AS NOTED DRAWN BY: GMS DESIGNED BY: TSW CHECKED BY: EKC STOCKTON, CALIFORNIA

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

TRAFFIC SIGNAL MODIFICATION

-CA: 1-800-227-2600-

1300 Clay Street, Suite 325 Oakland, California 94612

5365.25C

CALL TWO WORKING DAYS BEFORE YOU DIG

NUMBER OF CONDUCTORS CONDUCTOR DESIGNATION FREMONT ST AT FILBERT ST 28-CONDUCTOR CABLES POLE A | 1 | 1 | POLE C POLE E | | 1 | 1 | 1 POLE G TOTAL 28-CONDUCTOR CABLES | 4 | 2 | 1 | 1 | | 2 | 1 | 1 12-CONDUCTOR CABLES POLE B POLE D POLE F POLE H TOTAL 12-CONDUCTOR CABLES 3-CONDUCTOR CABLES POLE A POLE B | 1 | 1 | 1 | 1 1 1 1 POLE C POLE D POLE E | 1 | | | | 1 | 1 | 1 POLE F POLE G | | 1 | POLE H TOTAL 3-CONDUCTOR CABLES 8 4 3 2 1 3 2 1 NO. 10 CONDUCTORS LIGHTING (240V) TOTAL NO. 10 NO. 8 CONDUCTORS 2 | | LIGHT SERVICE TOTAL NO. 8 DETECTOR LEAD-IN CABLES 1 | 1 | 1 | 3 | 3 | 3 | 3 | 3 | 3 | 1 | 1 | 1 | 2 | TOTAL DLC 14 7 7 7 4 3 4 2 EVP CABLES 1_N 1_N 1_N 1_N 1_N | | 1_N 1_N 1_N 1_N | 1_N EVD TOTAL EVP CABLES 4 n 2 n 1 n 1 n 2 n 1 n 1 n APS CABLE (4C#18) 2n 2n 2n 2n FIBER OPTIC CABLE PTZ COMMUNICATION CABLE* |5| | | PERCENT FILL 24 | 22 | 17 | 24 | 14 | 21 | 16 | 17 2-4" 4" 4" 2.5" 2.5" 4" 3" 3" CONDUIT SIZE

CONDUCTOR SCHEDULE

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR

* POWER AND DATA CABLES (PER MANUFACTURER)

CONSTRUCTION NOTES: (THIS SHEET ONLY)

2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.

4 REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.

9 REMOVE AND SALVAGE EXISTING TYPE P TS1 TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. FURNISH AND INSTALL NEW TYPE P TS2 TRAFFIC SIGNAL CONTROLLER CABINET ON EXISTING FOUNDATION. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED.

11 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A. ON SHEET DT-1. FOR MOUNTING DETAILS.

16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).

FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET, FURNISH ALL CABLING AND MAKE ALL CONNECTIONS, SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.

27 REMOVE AND SALVAGE EXISTING PULL BOX. FURNISH AND INSTALL No. 6 PULL BOX.

28 REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING WIRING.


29 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN

36 ROUTE EXISTING COAXIAL CABLES, COILED IN PULL BOX, INTO CONTROLLER CABINET AND PROTECT IN PLACE.

44 REMOVE AND SALVAGE EXISTING IFS VIDEO MODEM (ONE-PORT) TO CORPORATION YARD. FURNISH AND INSTALL FIBER OPTIC VIDEO/DATA MODEM (8-PORT) IN CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS.

52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.

STEADY DEMAND SEQUENCE




EXISTING PHASE DIAGRAM

EVP ASSIGNMENTS

 $EVA = \emptyset 2 + \emptyset 5$

 $EVB = \emptyset 4$

 $EVC = \emptyset6 + \emptyset1$ $EVD = \emptyset 8$



1 inch = 20 ft.BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

(IN FEET)

TRAFFIC SIGNAL MODIFICATION

FREMONT STREET AT FILBERT STREET

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DATE: DECEMBER 2019 PW1516 SHEET NO. SCALE: AS NOTED CITY ENGINEER
STOCKTONI CHIER DRAWN BY:___ DESIGNED BY: TSW CHECKED BY: EKC SHEET 27 OF 36


CHECKED CITY APPROVAL
BY APPROVED BY DATE


Kimley» Horn 1300 Clay Street, Suite 325 Oakland, California 94612


Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF: 12/19/2019 DATE KEVIN G. AGUIGUI


No. 048732 9/30/22 R.C.E. No. 048732, EXP. 9/30/22








5365.286




REMOVAL PLAN SCALE: 1" = 40'




DETAIL "A" SCALE: 1'' = 5'

- 1 FURNISH AND INSTALL 2.5" RIGID METAL CONDUIT FOR FIBER OPTIC CABLE INTO NEW FOUNDATION PER DETAIL H, SHEET DT-4.
- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- 5 FURNISH AND INSTALL IP PTZ CAMERA ON LUMINAIRE ARM. SEE DETAIL D, ON SHEET DT-2, FOR MOUNTING DETAILS.
- 11 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 21 FURNISH AND INSTALL NEW PEDESTRIAN PUSH BUTTON POST WITH ONE ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 24 FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- 40 FURNISH AND INSTALL 107W LED LUMINAIRE ON EXISTING PG&E POLE.
- 41 FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER CABINET.
- 43 FURNISH AND INSTALL NEW TYPE P TRAFFIC SIGNAL CONTROLLER CABINET ON NEW FOUNDATION. SEE DETAIL H, SHEET DT-4, FOR FOUNDATION DETAIL. TERMINATE ALL WIRING INTO NEW CABINET.
- 53 FURNISH AND INSTALL NEW PUSH BUTTON CONDUCTORS BETWEEN ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) AND CABINET. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.
- 56 FURNISH AND INSTALL VIDEO DETECTION SYSTEM IN CONTROLLER CABINET. CONNECT CAMERAS AND CONFIGURE SYSTEM.
- 58 FURNISH AND INSTALL VIDEO DETECTION CAMERA ON TRAFFIC SIGNAL MAST ARM. SEE DETAIL E, SHEET DT-3, FOR MOUNTING DETAILS.
- 60 FURNISH AND INSTALL 2" CONDUIT WITH ONE (1) DETECTOR LOOP
- 61 EXTEND CONDUIT INTO NEW PULL BOX.



GRAM



PROPOSED PHASE DIAGRAM

EVP ASSIGNMENTS

CA: 1-800-227-2600-

CA: 1-800-227-2600-CALL TWO WORKING


DAYS BEFORE YOU DIG

 $EVB = \emptyset4$

 $EVA = \emptyset 2 + \emptyset 5$ $EVC = \emptyset6 + \emptyset1$ $EVD = \emptyset 8$

	NO.	DESCRIPTION	CHECKED	CITY APPRO	
			BY	APPROVED BY	DATE
REVISIONS					
<u>is</u>			<u> </u>		
╽┈┝					
-					

Oakland, California 94612 Phone: (510) 625-0712



DATE KEVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

SCALE: AS NOTED No. 048732 DRAWN BY:__ DESIGNED BY: TSW

185' TO LIMIT LINE

] || |

| || |

25' TO LIMIT LINE (TYP.)

R10-12

185' TO

0 | |

R3-4

53 41

55' VIDEO DETECTION -

ZONE (TYP.)

LAFAYETTE STREET

SEE DETAIL 'A', -

THIS SHEET

I LIMIT LINE

TRAFFIC SIGNAL MODIFICATION FILBERT STREET AT LAFAYETTE STREET

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

> DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA


DATE: DECEMBER 2019

PROJECT NO.

GRAPHIC SCALE

(IN FEET) 1 inch = 20 ft.

	STEADT DEMAND SEQUENCE
	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
<u>!</u>	EXISTING PHASE DIAC



1300 Clay Street, Suite 325

COND	UCTOR	SC	HED	ULE							
			NUM	1BER	OF	СО	NDU	СТО	RS		_
CONDUCTOR DESIGNATION	FILI	BER	T ST	REE	ТА	T LA	\FA\	ΈTΤ	E S	TREE	-
	$\sqrt{1}$	$\sqrt{2}$	3	4	/5\	6	\overline{A}	/8\	/9\		Γ
NO. 14 CONDUCTORS											r
Ø1	3				3	3					r
ø2	3				3	3	3	3	3		r
Ø4	3	3	3								ľ
ø5	6	3	3	3	3	3	3	3	3		Ī
ø6	3				3						
Ø8	3				3	3	3	3			
ø2P	2				2	2	2	2	2		
Ø4P	4	2	2		2	2	2	2			
Ø6P	4	2	2	2	2						
Ø8P	4	2			2	2	2				
ø2 PPB	1				1	1	1	1			Ī
ø4 PPB	2	1	1	1	1	1	1	1	1		r
ø6 PPB	1	1	1								r
Ø8 PPB	2	1			1	1					T
PPB COMMON	2	1	1	1	1	1	1	1	1		T
SPARES	6	3	3	3	3	3	3	3	3		T
PEU	3		Ė		3	-		Ť			T
											T
TOTAL NO. 14	52	19	16	10	33	25	21	19	13		<u></u>
NO. 10 CONDUCTORS											ł
SIGNAL COMMON	2	1	1	1	1	1	1	1	1		+
SIGNAL COMMON	- -	<u> </u>				<u></u>		<u> </u>			ł
TOTAL NO. 10	2	1	1	1	1	1	1	1	1		ļ
NO 9 CONDUCTORS											ļ
NO. 8 CONDUCTORS		_						_			ŀ
LIGHTING (240V) 120V SIGNAL SERVICE		2	2		2	2	2	2	2		ł
120V SIGNAL SERVICE	3										ł
TOTAL NO. 8	3	2	2		2	2	2	2	2		ł
TOTAL NO. O	- 3				-						ł
EVP CABLES	+				_						ł
EVA	1				1	1	1	1	1		H
EVB	1	1	1		-				1		ł
EVC .	1	-			1		_			-	+
EVD	1				1	1	1				f
		<u> </u>				-					t
TOTAL EVP CABLES	4	1	1		3	2	2	1	1		t
TOTAL EN CADLES	+				-						t
VIDEO DETECTION CABLE**											t
Ø2, Ø5	1				1	1	1	1	1		t
Ø4	1	1	1	\vdash	<u> </u>			 	-		t
ø6, ø1	1	<u> </u>	-		1						t
Ø8	1		<u> </u>		1	1	1		-		t
F U				 	-	-					+
DETECTION LOOP CABLE											+
ø2	1				1	1	1	1	1		-
ø6	1				1						
APS CABLE (4C#18)		1		2	1		2		2		-
PTZ COMMUNICATION CABLE*	1				1						
FIBER OPTIC CABLE											
PERCENT FILL	9	11	9	5	23	14	15	11	10		ſ
CONDUIT SIZE	2 4	3"	3"	ע "	3"	3"	マ"	マ"	7"		٢


ALL	CONDUITS	& CONDU	JCTORS	ARE I	NEW	UNLESS	OTHERWISE	NOTED.	
~	DEMOTEC	CVICTIMO	CONDUC	TOD					

- E DENOTES EXISTING CONDUCTOR
- * POWER AND DATA CABLES (PER MANUFACTURER)
- ** CABLES PER MANUFACTURER

			,			F	POLE A	ND EQ	UIPME	NT SC	CHEDU	JLE	
		STANDARD		LOCA	ATION	LED	VEHICLE SIGN	AL MOUNTING	PED	А	PS	STREET NAME SIGN	TODEOUT DESCRIPTION
LOCATION	TYPE	SIGNAL MAST ARM	LUMINAIRE MAST ARM	А	В	LUMINAIRE WATTAGE	MAST ARM	POLE	SIGNAL MOUNTING	ø	ARROW	(S.N.S.) LEGEND	*SPECIAL REQUIREMENTS
A	PPB POST			5.6'	2.6'	_	_		- Table	8	LEFT	_	
В	1-B	_	_	1.6'	2.7'	_	_	TV-1-T	SP-1-T	6	RIGHT	_	
0	19-4-100	25'	12'	2.65'	2.6'	107W	MAS	SV-1-T	SP-1-T	6	LEFT	FILBERT ST 200	FURNISH AND INSTALL R3-4 SIGN, R10-12 SIGN, EVP, AND VIDEO DETECTION CAMERA ON SIGNAL MAST ARM.
D	1-B	_	_	0,	2.6'	_	-	TV-1-T	SP-1-T	4	RIGHT	_	
E	23-4-100	35'	_	0.8'	3.3'	107W	MAS MAS	SV-1-T	SP-1-T	4	LEFT	LAFAYETTE ST 2500	FURNISH AND INSTALL IP PTZ CAMERA ON LUMINAIRE ARM. FURNISH AND INSTALL R3-4 SIGN, EVP, AND VIDEO DETECTION CAMERA ON SIGNAL MAST ARM.
F	1-B		_	-0.3'	3.2'	_	_	TV-1-T	SP-1-T	2	RIGHT	_	
G	19-4-100	25'	12'	0.8'	3'	107W	MAS	SV-1-T	SP-1-T	2	LEFT	FILBERT ST 300	FURNISH AND INSTALL R3-4 SIGN, R10-12 SIGN, EVP, AND VIDEO DETECTION CAMERA ON SIGNAL MAST ARM.
H	1-B	_	_	4.1'	2.65'	_	_	TV-1-T	SP-1-T	8	RIGHT	_	
	23-4-100	35'	_	-12.35	3.5'	-	MAS MAS	SV-1-T	SP-1-T	_		LAFAYETTE ST 2400	FURNISH AND INSTALL R3-4 SIGN, EVP, AND VIDEO DETECTION CAMERA ON SIGNAL MAST ARM.

- * OTHER REQUIREMENTS ARE COVERED BY NOTES, LEGEND, SPECIAL PROVISIONS AND CALTRANS STANDARD SPECIFICATIONS. FOR TYPE OF STANDARD, VEHICLE AND PEDESTRIAN MOUNTING, SEE CALTRANS STANDARD PLANS.
- ALL EQUIPMENT IS NEW UNLESS OTHERWISE NOTED.
- PEDESTRIAN PUSH BUTTONS SHALL MEET ADA ACCESSIBILITY GUIDELINES. MOUNTING HEIGHT OF PPB IS 40" ABOVE FINISHED SIDEWALK SURFACE.
- R3-4 OR R10-12 M.A. SIGN SHALL BE INSTALLED 3'6" FROM END OF MAST ARM, (CENTER TO CENTER) UNLESS OTHERWISE SHOWN.
- ALL VEHICLE INDICATIONS SHALL BE 12" L.E.D.
- PEDESTRIAN PUSH BUTTON SIGNS SHALL MEET MUTCD R10-3b, UNLESS OTHERWISE INDICATED BY THE ENGINEER.
- PEDESTRIAN PUSH BUTTON SIGNS SHALL FIT ON THE 9"X12" HOUSING WITHOUT ANY MODIFICATIONS.
- PEDESTRIAN HEADS SHALL BE COUNTDOWN TYPE.
- MAST ARM STREET NAME SIGNS ARE TO BE PER STOCKTON STANDARD DRAWING R-94.
- 1-B STREET NAME SIGNS ARE TO BE PER STOCKTON STANDARD DRAWING R-109 (DETAIL A).

	DETECT	OR TABLE	
DETECTOR NO.	Ø	NUMBER OF DETECTORS	DETECTOR TYPE
1	1A	1	
2	2A	1	
3	4A	1	
4	5A	1	
5	6A	1	
6	8A	1	
7	1B	1	BIKE
8	2B	1	BIKE
9	4B	1	BIKE
10	6B	1	BIKE
11	8B	1	BIKE
12	2D	1	SAMPLER
13	6C	1	SAMPLER



SIGNAL STANDARD PLACEMENT DIMENSIONS (CALTRANS STANDARD PLAN ES-4C)

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

TRAFFIC SIGNAL SCHEDULE

FILBERT STREET AT LAFAYETTE STREET SCH

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DATE: DECEMBER 2019 SCALE: AS NOTED DESIGNED BY: TSW

CITY ENGINEER
STOCKTON, CALIFORNIA

PW1516 SHEET NO.

SHEET 31 OF 36

CHECKED CITY APPROVAL
BY APPROVED BY DATE

1300 Clay Street, Suite 325 Oakland, California 94612

Phone: (510) 625-0712

KEVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22


DESIGNED UNDER THE SUPERVISION OF: 12/19/2019 No. 048732 9/30/22 DATE

5365.30C


CA: 1-800-227-2600-CALL TWO WORKING DAYS BEFORE YOU DIG


CA: 1-800-227-2600

- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- 4 REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC eX2 CONTROLLER WITH LATEST UERSION D4 FIRMWARE IN CONTROLLER CABINET.
- 9 REMOVE AND SALVAGE EXISTING TYPE P TS1 TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. FURNISH AND INSTALL NEW TYPE P TS2 TRAFFIC SIGNAL CONTROLLER CABINET ON EXISTING FOUNDATION. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED
- 11 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 12 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL FRAME. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 21 FURNISH AND INSTALL NEW PEDESTRIAN PUSH BUTTON POST WITH ONE ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 28 REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING WIRING.
- 29 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 40 FURNISH AND INSTALL 107W LED LUMINAIRE ON EXISTING PG&E POLE.
- 41 FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 45 FURNISH AND INSTALL VIDEO DETECTION CAMERA ON LUMINAIRE MAST ARM. SEE DETAIL E, SHEET DT-3, FOR MOUNTING DETAILS.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER
- 53 FURNISH AND INSTALL NEW PUSH BUTTON CONDUCTORS BETWEEN ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) AND CABINET. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.
- 56 FURNISH AND INSTALL VIDEO DETECTION SYSTEM IN CONTROLLER CABINET. CONNECT CAMERAS AND CONFIGURE SYSTEM.
- 58 FURNISH AND INSTALL VIDEO DETECTION CAMERA ON TRAFFIC SIGNAL MAST ARM. SEE DETAIL E, SHEET DT-3, FOR MOUNTING DETAILS.
- 60 FURNISH AND INSTALL 2" CONDUIT WITH ONE (1) DETECTOR LOOP CABLE.
- 61 EXTEND CONDUIT INTO NEW PULL BOX.
- 66 FURNISH AND INSTALL 2" CONDUIT WITH TWO (2) DETECTOR LOOP CABLES.
- 67 REMOVE AND SALVAGE EXISTING IFS VIDEO MODEM (ONE-PORT) TO CORPORATION YARD. FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- 70 CUT BACK EXISTING CONDUIT AS NECESSARY TO COUPLE WITH SPLIT CONDUIT. PROTECT EXISTING FIBER IN CONDUIT. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 71 FURNISH AND INSTALL 2" SPLIT CONDUIT AROUND EXISTING FIBER OPTIC CABLE AND EXTEND CONDUIT INTO NEW PULL BOX. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 72 REINSTALL FIBER OPTIC CABLE IN EXISTING 2" CONDUIT. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).



REMOVAL PLAN SCALE: 1" = 40'






CITY APPROVAL

BY APPROVED BY DATE

LIMIT LINE

EX. 2"c, 2 dlc-



MAIN STREET

└EX. 2"c, 2 dlc

EXISTING PHASE DIAGRAM

55' VIDEO DETECTION

SEE DETAIL 'A',

THIS SHEET

ZONE (TYP.)

53 41

FEX. 2"c, f.o. CABLE

STEADY DEMAND SEQUENCE

Ø2 $\Rightarrow \frac{\emptyset 2P}{} \Rightarrow \frac{1}{} \Rightarrow \frac{1}{$


PROPOSED PHASE DIAGRAM

EVP ASSIGNMENTS

- $EVA = \emptyset2$
- $EVB = \emptyset4$
- $EVC = \emptyset6$ $EVD = \emptyset 8$

Kimley»Horn
1300 Clay Street, Suite 325 © 2019

Oakland, California 94612 Phone: (510) 625-0712





BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

_EX. 2"c, 2 dlc

LINE (TYP.)

__EX. 2"c, 2 dlc

6B

LIMIT LINE

| Table | Tabl

GRAPHIC SCALE

(IN FEET)

1 inch = 20 ft.

SHEET 32 OF 30

TRAFFIC SIGNAL MODIFICATION

FILBERT STREET AT MAIN STREET

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

STOCKTON, CALIFORNIA

DATE: DECEMBER 2019 SCALE: AS NOTED DRAWN BY: ____GMS DESIGNED BY: TSW

5365:31C



				ULE							
CONDUCTOR DESIGNATION						CO T FI					
	/1E	2	3	4	5	6	<u> </u>	8			Γ
NO. 14 CONDUCTORS											L
ø1											\perp
ø2	6	3	3	3	3	3	3	3			igdash
ø4	3			<u> </u>		3	3				╄
ø5	-	<u> </u>		-							╀
ø6	3	3	-7	7		7					╀
Ø8	6	3	3	3	_	3				-	╁
ø2P ø4P	4	2	2	2	2	2	2				╁
<u>94</u> г ø6Р	4				-	2	2	2			t
Ø8P	2	2			-						+
ø2 PPB	1	1	1	1	ļ						t
ø4 PPB	2	1	1	1	1	1	1	1			T
Ø6 PPB	1			 '	 	1	1	Ė			T
Ø8 PPB	1	1			<u> </u>		Ė				T
PPB COMMON	2	1	1	1	1	1	1	1			T
SPARES	6	3	3.	3	3	3	3	3			Γ
PEU	3										$oxed{\Gamma}$
TOTAL NO. 14	46	22	16	16	12	19	16	10			
NO. 10 CONDUCTORS											-
SIGNAL COMMON	2	1	1	1	1	1	1	1			T
TOTAL NO. 10	2	1	1	1	- 1	1	1	1			H
NO O CONDUCTORO											_
NO. 8 CONDUCTORS											╀
LIGHTING (240V) 120V SIGNAL SERVICE		2	2	2	2	2					╀
120V SIGNAL SERVICE	3										+
TOTAL NO. 8	3	2	2	2	2	2					
EVP CABLES											+
EVA	1	1	1	1	1					ļ	T
EVB	1	· ·	· ·	 	 	1	1				T
EVC	1										\top
EVD	1	1	1	1							I
TOTAL EVP CABLES	4	2	2	2	1	1	1				
VIDEO DETECTION CABLE**	-			<u> </u>							+
ø2, ø5	1	1	1	1	1						T
Ø 4	1					1					I
ø6, ø1	1										\prod
Ø8	1	1	1	1							+
DETECTOR LOOP CABLE											#
ø2		2,2 _E	2	2	2	<u> </u>					\downarrow
ø4 	1	<u> </u>				1	1	-			+
<u>Ø6</u> Ø8	2,2 _E	1	1		<u> </u>	2 _E	2 E	—		 	+
		Ė				<u> </u>		_			#
APS CABLE (4C#18)	-	4	1	4	1	1		2	<u> </u>		+
PTZ COMMUNICATION CABLE*	_ 1_	1	1	1	1						+
FIBER OPTIC CABLE				1				-		_	+
PERCENT FILL	12	20	16	15	12	17	C	1			+
CONDUIT SIZE	42 2-2°	3"	16 3"	15 3"	12 3"	3"	9 3"	3"		-	+


,	ALL	CONDUITS	&	CONDUCTORS	ARE	NEW	UNLESS	OTHERWISE	NOTED.

E - DENOTES EXISTING CONDUIT OR CONDUCTORS

				•			POLE	E AND E	EQUIPM	1ENT	SCHE	DULE	
		STANDARD		LOCA	NOITA	LED	VEHICLE SIGN	IAL MOUNTING	PED	А	.PS	STREET NAME SIGN	*CDECIAL DECUMPENTO
LOCATION	TYPE	SIGNAL MAST ARM	LUMINAIRE MAST ARM	А	В	LUMINAIRE WATTAGE	MAST ARM	POLE	SIGNAL MOUNTING	ø	ARROW	(S.N.S.) LEGEND	*SPECIAL REQUIREMENTS
A	1-B	_	_	12'	8.1'	_	_	-	SP-2-T	8	RIGHT	_	INSTALL RELOCATED PEDESTRIAN SIGNAL HEADS FROM POLE B.
(B) _E	19-3-80 E	25' E	12'	-9.3' _E	4.8' E	_	MAS E	SV-1-T				FILBERT ST 400 S	FURNISH AND INSTALL R10-12 SIGN AND VIDEO DETECTION CAMERA ON SIGNAL MAST ARM.
©	1-B	_	_	-0.5	6.1'	_		TV-2-T	SP-2-T	8	RIGHT	_	
0	PPB POST	_	_	-4.9'	3.9'		_	_	_	2	LEFT	_	
E	15TS	_	12'	17.2'	2.85'	107W	_	TV-1-T	-	2	RIGHT	MAIN ST 2500 E	FURNISH AND INSTALL VIDEO DETECTION CAMERA ON LUMINAIRE ARM. FURNISH AND INSTALL EVP ON Ø4 SIGNAL HEAD. FURNISH AND INSTALL STREET NAME SIGN PER CITY OF STOCKTON STANDARD DRAWING R109 (DETAIL A).
(F) E	19-3-80 E	25'	12'	-5.2' E	2.5' E	107W	MAS E	SV-1-T	SP-2-T	4	RIGHT	FILBERT ST 500 S	FURNISH AND INSTALL R10-12 SIGN AND VIDEO DETECTION CAMERA ON SIGNAL MAST ARM. FURNISH AND INSTALL STREET NAME SIGN PER CITY OF STOCKTON STANDARD DRAWING R-94.
G	15TS	_	_	-8.5'	2.7'	107W	_	TV-1-T	SP-1-T	4	RIGHT	-	•
H	1-B	_	_	-15.5	2.9'	_		TV-1-T	SP-1-T	6	LEFT	_	FURNISH AND INSTALL EVP ON Ø8 SIGNAL HEAD.
	15TS	_	12'	3.3'	5'	107W	_	TV-2-T	_	6	RIGHT	MAIN ST 2400 E	FURNISH AND INSTALL VIDEO DETECTION CAMERA ON LUMINAIRE ARM. INSTALL RELOCATED STREET NAME SIGN FROM POLE B.

- * OTHER REQUIREMENTS ARE COVERED BY NOTES, LEGEND, SPECIAL PROVISIONS AND CALTRANS STANDARD SPECIFICATIONS. FOR TYPE OF STANDARD, VEHICLE AND PEDESTRIAN MOUNTING, SEE CALTRANS STANDARD PLANS.
- E = DENOTES EXISTING EQUIPMENT
- R = DEMOTES RELOCATED EQUIPMENT
- ALL EQUIPMENT IS NEW UNLESS OTHERWISE NOTED.
- PEDESTRIAN PUSH BUTTONS SHALL MEET ADA ACCESSIBILITY GUIDELÍNES.
- MOUNTING HEIGHT OF PPB IS 40" ABOVE FINISHED SIDEWALK SURFACE. - R10-12 M.A. SIGN SHALL BE INSTALLED 3'6" FROM END OF MAST ARM.
- (CENTER TO CENTER) UNLESS OTHERWISE SHOWN.
- ALL VEHICLE INDICATIONS SHALL BE 12" L.E.D.
- PEDESTRIAN PUSH BUTTON SIGNS SHALL MEET MUTCD R10-3b, UNLESS
- OTHERWISE INDICATED BY THE ENGINEER.
- PEDESTRIAN PUSH BUTTON SIGNS SHALL FIT ON THE 9"X12" HOUSING WITHOUT ANY MODIFICATIONS.
- PEDESTRIAN HEADS SHALL BE COUNTDOWN TYPE.
- MAST ARM STREET NAME SIGNS ARE TO BE PER STOCKTON STANDARD DRAWING R-94.
- 1-B OR 15TS STREET NAME SIGNS ARE TO BE PER STOCKTON STANDARD DRAWING R-109 (DETAIL A).

DETECTOR TABLE DETECTOR A NUMBER OF DETECTOR											
ø	NUMBER OF DETECTORS	DETECTOR TYPE									
2A	1										
2B	1										
4A	1										
6A	1										
6B	1										
8A	2										
2C	2	BIKE									
4B	1	BIKE									
6C	2	BIKE									
8B	2	BIKE									
2D	1	SAMPLER									
2E	1	SAMPLER									
4C	1	SAMPLER									
6D	1	SAMPLER									
6E	1	SAMPLER									
8C	1	SAMPLER									
	Ø 2A 2B 4A 6A 6B 8A 2C 4B 6C 8B 2D 2E 4C 6D 6E	Ø NUMBER OF DETECTORS 2A 1 2B 1 4A 1 6A 1 6B 1 8A 2 2C 2 4B 1 6C 2 8B 2 2D 1 2E 1 4C 1 6D 1 6E 1									



SIGNAL STANDARD PLACEMENT DIMENSIONS

(CALTRANS STANDARD PLAN ES-4C)

CHECKED CITY APPROVAL
BY APPROVED BY D DESCRIPTION

1300 Clay Street, Suite 325 Oakland, California 94612

Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF:

12/19/2019 DATE

FILBERT STREET AT MAIN STREET SCH DATE: DECEMBER 2019 SCALE: AS NOTED No. 048732 9/30/22

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DRAWN BY: GMS CITY ENGINEER STOCKTON, CALIFORNIA DESIGNED BY: TSW CHECKED BY: EKC

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY,

FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

TRAFFIC SIGNAL SCHEDULE

PROJECT NO.



KEVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

^{*} POWER AND DATA CABLES (PER MANUFACTURER)

^{**} CABLES PER MANUFACTURER

- 2 FURNISH AND INSTALL OPTICOM MODEL 764 MULTIMODE PHASE SELECTOR IN TRAFFIC SIGNAL CONTROLLER CABINET.
- 4 REMOVE AND SALVAGE EXISTING TRAFFIC SIGNAL CONTROLLER TO CORPORATION YARD. FURNISH AND INSTALL NEW ATC ex2 CONTROLLER WITH LATEST VERSION D4 FIRMWARE IN CONTROLLER
- 9 REMOVE AND SALVAGE EXISTING TYPE P TS1 TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. FURNISH AND INSTALL NEW TYPE P TS2 TRAFFIC SIGNAL CONTROLLER CABINET ON EXISTING FOUNDATION. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED.
- 11 FURNISH AND INSTALL OPTICOM MODEL 721 OPTICAL DETECTOR ON TRAFFIC SIGNAL MAST ARM. CONNECT TO EVP CABLE AND ORIENT TO SIGNAL PHASE AS INDICATED ON PLAN. SEE DETAIL A, ON SHEET DT-1, FOR MOUNTING DETAILS.
- 14 REMOVE AND DISPOSE OF EXISTING PULL BOX. FURNISH AND INSTALL No. 5 PULL BOX.
- 16 FIBER TO BE COILED IN PULL BOX DURING CONSTRUCTION AT TRAFFIC SIGNAL CONTROLLER CABINET. CONTRACTOR TO REINSTALL FIBER OPTIC CABLE INTO NEW CABINET AFTER CABINET IS COMPLETE. ANY DAMAGE TO EXISTING FIBER OPTIC CABLES SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE. REFER TO SPECIAL PROVISIONS SECTION 77-1.24 (FIBER OPTIC CABLING).
- 17 REMOVE EXISTING 8" SIGNAL HEADS AND TV-2-T MOUNTING FRAME. SIGNAL HEADS TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW TV-2-T MOUNTING FRAME. CONNECT NEW SIGNAL HEADS TO EXISTING WIRING.

CONDUCTOR DESIGNATION	NUMBER OF CONDUCTORS MAIN ST AT GOLDEN GATE AVE									
GONDOOTOR DESIGNATION	-								VE.	
NO. 44 CONSUCTORS	/1\	/2\ 	/3\	/4\ <u></u>	/5\	/6\ <u></u>	/ / /	/8\	/9	
NO. 14 CONDUCTORS							_		_	
ø1	6	3	3	3	3	3	3	3	3	
ø2	3	3	3	3						
<u> </u>	3				3	3	3	3	3	
ø5	3				3	3				
ø6	3				3	3	3	3	3	
ø8	3	3	3							
ø2P	2	2	2	2					_	
ø4P	4	2			2	2	2			
ø6P	2				2	2	2	2	2	
ø8P	_ 4	2	2	2	2	2	2	2	2	
ø2 PPB	1	1	1							
ø4 PPB	1				1	1				
Ø6 PPB	1				1	1	1	1	-	
Ø8 PPB	2	1	1	1	1	1	1	1	-	
PEU	3	Ė		<u> </u>	<u>'</u>	•	'	-	\vdash	
	+								\vdash	
SPARES	6	6	6	6	6	6	6	6	6	
TOTAL NO. 14	47	23	21	17	27	27	23	21	2	
NO 12 CONDUCTORS										
NO. 12 CONDUCTORS										
PPB COMMON	2	1	1	1	1	1	1	1	-	
TOTAL NO. 12	2	1	1	1	1	1	1	1		
NO. 10 CONDUCTORS	_								\vdash	
					_	_			<u> </u>	
LIGHTING (240V) SIGNAL COMMON	4		2	2	2	2	2	2	2	
SIGNAL COMMON	2	1	1	1	1	1	1	1	-	
TOTAL NO. 10	6	1	3	3	3	3	3	3		
DETECTOR LEAD-IN CABLES	+								_	
ø1	1				1	1				
ø2	3	1	1	1					Γ	
Ø4	1	1	<u> </u>	r i					\vdash	
ø5	1	1	1	1					\vdash	
ø6	3	'	<u>'</u>		3	2	2	2	2	
Ø8	1				1	1	1	1	-	
								_		
TOTAL DLC	10	3	2	2	5	4	3	3		
EVP CABLES										
EVA	1 _N									
EVB	1 _N				1 _N	1 _N	1 _N			
EVC	1 _N		ļ		1 _N					
EVD	1 _N		1 _N		' N	'N	I N	' N	-	
	'N	'N	' N						-	
TOTAL EVP CABLES	4 _N	1 _N	1 _N		2 _N	2 _N	2 _N	1 _N		
APS CABLE (4C#18)		0		2			2		-	
FIBER OPTIC CABLE	1	2 _N		2 _N			2 _N		2	
PTZ COMMUNICATION CABLE*	1 1				1	1	1		-	
					1	1				
PERCENT FILL	28	18	15	13	27	25	23	17	1	
									2	

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS OTHERWISE NOTED.

N - DENOTES NEW CONDUCTOR * POWER AND DATA CABLES (PER MANUFACTURER)

- FURNISH AND INSTALL MANAGED FIBER ETHERNET SWITCH IN THE CONTROLLER CABINET. FURNISH ALL CABLING AND MAKE ALL CONNECTIONS. SEE SPECIAL PROVISIONS AND SYSTEM DIAGRAMS, ON SHEETS SY-1 AND SY-2, FOR DETAILS.
- 25 REMOVE AND SALVAGE EXISTING STREET NAME SIGNS FROM EXISTING POST. REMOVE AND RELOCATE EXISTING POST TO NEW LOCATION AS SHOWN ON PLAN.
- 27 REMOVE AND SALVAGE EXISTING PULL BOX. FURNISH AND INSTALL No. 6 PULL BOX.
- 28 REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING WIRING.
- REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.
- 33 REMOVE EXISTING 8" SIGNAL HEADS AND SV-2-TB MOUNTING FRAME. SIGNAL HEADS TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL TWO NEW 12" 3-SECTION SIGNAL HEADS ON NEW SV-2-TB MOUNTING FRAME. CONNECT NEW SIGNAL HEADS TO EXISTING WIRING.
- 46 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTONS. FURNISH AND INSTALL TWO (2) ACCESSIBLE PEDESTRIAN SIGNAL SYSTEMS.
- 52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.


STEADY DEMAND SEQUENCE

EVP ASSIGNMENTS

 $EVA = \emptyset2 + \emptyset5$

 $EVB = \emptyset4$ $EVC = \emptyset6 + \emptyset1$ $EVD = \emptyset 8$

EXISTING PHASE DIAGRAM



CHECKED CITY APPROVAL

APPROVED BY

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625-0712

DESIGNED UNDER THE SUPERVISION OF:

R.C.E. No. 048732, EXP. 9/30/22

12/19/2019 KEVIN G. AGUIGUI DATE

MAIN STREET AT GOLDEN GATE AVENUE DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

TRAFFIC SIGNAL MODIFICATION

GRAPHIC SCALE

(IN FEET) 1 inch = 20 ft.

DATE: DECEMBER 2019 PROJECT NO. SCALE: AS NOTED SHEET NO. DRAWN BY: GMS CITY ENGINEER STOCKTON, CALIFORNIA DESIGNED BY: TSW CHECKED BY: EKC

5365.33C

-CA: 1-800-227-2600-CALL TWO WORKING

DAYS BEFORE YOU DIG



CONDUCTOR SCHEDULE NUMBER OF CONDUCTORS CONDUCTOR DESIGNATION NO. 14 CONDUCTORS Ø4P Ø6P Ø8P 4N2Nø2 PPB Ø4 PPB ø6 PPB $3,3_{N}$ 3 3 3 3_{N} 3_{N} 3_{N} 3_{N} SPARES TOTAL NO. 14 NO. 12 CONDUCTORS PPB COMMON TOTAL NO. 12 NO. 10 CONDUCTORS LIGHTING (240V) SIGNAL COMMON TOTAL NO. 10 DETECTOR LEAD-IN CABLES | 1 | 1 | 1 | 1 | TOTAL DLC EVP CABLES 1_N 1_N 1_N

EXISTING CONDUITS & CONDUCTORS TO REMAIN IN PLACE UNLESS

R - DENOTES REMOVE UNUSED CONDUCTORS FROM EXISTING CONDUIT

* POWER AND DATA CABLES (PER MANUFACTURER)

27 REMOVE AND SALVAGE EXISTING PULL BOX. FURNISH AND INSTALL No. 6 PULL BOX.

28 REMOVE EXISTING 8" SIGNAL HEAD AND SV-1-T MOUNTING FRAME. SIGNAL HEAD TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL NEW 12" 3-SECTION SIGNAL HEAD ON NEW SV-1-T MOUNTING FRAME. CONNECT NEW SIGNAL HEAD TO EXISTING WIRING.

29 REMOVE AND SALVAGE EXISTING PEDESTRIAN PUSH BUTTON. FURNISH AND INSTALL ACCESSIBLE PEDESTRIAN SIGNAL SYSTEM.

30 REMOVE AND SALVAGE EXISTING TYPE P TRAFFIC SIGNAL CONTROLLER CABINET TO CORPORATION YARD. MODIFY EXISTING FOUNDATION PER DETAIL I, ON SHEET DT-4. FURNISH AND INSTALL NEW TYPE P TRAFFIC SIGNAL CONTROLLER CABINET ON MODIFIED FOUNDATION. TERMINATE ALL WIRING INTO NEW CABINET. RELOCATE ALL EXISTING EQUIPMENT INTO NEW CABINET UNLESS OTHERWISE NOTED.

REMOVE EXISTING 8" SIGNAL HEADS AND SV-2-TB MOUNTING FRAME. SIGNAL HEADS TO BECOME PROPERTY OF CONTRACTOR. FURNISH AND INSTALL TWO NEW 12" 3-SECTION SIGNAL HEADS ON NEW SV-2-TB MOUNTING FRAME. CONNECT NEW SIGNAL HEADS TO EXISTING WIRING.

FURNISH AND INSTALL 4" DIAMETER PEDESTRIAN PUSH BUTTON POST WITH TWO (2) ACCESSIBLE PEDESTRIAN SIGNAL SYSTEMS.

39 REMOVE AND SALVAGE EXSITING PEDESTRIAN PUSH BUTTONS. PATCH HOLE IN SIGNAL POLE.

47 SPLICE Ø VEHICLE CONDUCTORS IN THE PULL BOX AND REWIRE SIGNAL HEAD TO Ø.

<u>Ø2</u>

____ø2

STEADY DEMAND SEQUENCE

<u> Ø2</u>

STEADY DEMAND SEQUENCE

<u>Ø2</u>

EVP ASSIGNMENTS

 $EVA = \emptyset2 + \emptyset5$ $EVB = \emptyset4$

 $EVC = \emptyset6 + \emptyset1$

 $EVD = \emptyset8$

PROPOSED PHASE DIAGRAM

EXISTING PHASE DIAGRAM


52 CONNECT ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) TO EXISTING PUSH BUTTON CONDUCTORS. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.

53 FURNISH AND INSTALL NEW PUSH BUTTON CONDUCTORS BETWEEN ACCESSIBLE PEDESTRIAN SIGNAL (APS) SYSTEM(S) AND CABINET. FURNISH AND INSTALL NEW APS CONDUCTORS BETWEEN PUSH BUTTON(S) AND CORRESPONDING PEDESTRIAN SIGNAL HEAD(S) AS REQUIRED BY THE APS MANUFACTURER.

|52|29|26|17 52 33 29 26 30 24 20 4 2 −EX. 2"c, f.o. CABLE ø5 << |----52 29 26 17 MAIN STREET 52 29 28 26 17 26 39 CURB/BERM FLOW LINE OR ÉDGE OF SHOULER-GRAPHIC SCALE FOR "A" AND "B" LOCATION DIMENSIONS, SEE POLE TYPE (IN FEET) POLE SCHEDULE 1 inch = 20 ft.BEGIN CURB OR AS DIRECTED RETURN BY THE ENGINEER. PPB POST 7.1' BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, SIGNAL STANDARD REMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS -0.7'PPB POST PLACEMENT DIMENSIONS



DAYS BEFORE YOU DIG




TOTAL EVP CABLES

APS CABLE (4C#18)



1300 Clay Street, Suite 325 Oakland, California 94612



R.C.E. No. 048732, EXP. 9/30/22

DATE: DECEMBER 2019 SCALE: AS NOTED No. 048732 9/30/22 DESIGNED BY: TSW

TRAFFIC SIGNAL MODIFICATION MAIN STREET AT NETHERTON AVENUE DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

PW1516 SHEET NO. CITY ENGINEER
STOCKTON, CALIFORNIA SHEET 35 OF 3

5365.396

Phone: (510) 625-0712

(CALTRANS STANDARD PLAN ES-4C)

		PROPOSED EQUIPMENT											
LOCATION	EVP/TSP DETECTOR	PHASE SELECTOR	AUXILIARY PANEL*	CABINET TYPE	CONTROLLER	MANAGED FIBER ETHERNET SWITCH	IP PTZ CAMERA	FIBER VIDEO/DATA MODEM (8 PORT)	12" SIGNAL HEAD	SFP (RJ45) WITH CAT5E (RED)	SFP (SMFO RECEIVE)	SFP (SMFO TRANSMIT)	APS
WEBER AVENUE / CENTER STREET				Р	ATC eX2	1							8
WEBER AVENUE / EL DORADO STREET	3	1	1		ATC eX2					1			8
WEBER AVENUE / SAN JOAQUIN STREET	4	1		M (TALL)	ATC eX2					1			8
WEBER AVENUE / SUTTER STREET			1		ATC eX2		_						8
MINER AVENUE / AIRPORT WAY			1			1	1		4	1	1	1	8
MINER AVENUE / WILSON WAY					ATC eX2				12			,	8
FREMONT STREET / WILSON WAY			1		ATC eX2				3				8
FREMONT STREET / EASTLAND DRIVE	4	1		Р	ATC eX2	1	1		8	2	1	1	
FREMONT STREET / E STREET	3	1		Р	ATC eX2	1	1		3	2	1	1	4
FREMONT STREET / FILBERT STREET	4	1		Р	ATC eX2	1		1	3	1	1	1	8
FILBERT STREET / MINER AVENUE													
FILBERT STREET / MYRTLE (WEBER)													1
FILBERT STREET / MYRTLE (SR4 WB)													
FILBERT STREET / MARKET STREET (SR4 EB)													1
FILBERT STREET / LAFAYETTE STREET	4	1		Р	ATC eX2	1	1		14	1	1	1	8
FILBERT STREET / MAIN STREET	4	1		Р	ATC eX2	1			7	1	1	1	8
MAIN STREET / GOLDEN GATE AVENUE	4	1		Р	ATC eX2	1			9	1			8
MAIN STREET / NETHERTON AVENUE	4	1		Р	ATC eX2	1	1		13	1	1	1	8
CITY OF STOCKTON TMC						2		1			1	1	
TOTALS:	34	9	4	9	13	11	5	2	76	12	8	8	100

NOTE: THIS LIST IS FOR EQUIPMENT ONLY.

* CITY-FURNISHED, CONTRACTOR INSTALLED (SEE TECHNICAL SPECIAL PROVISIONS SECTION 6-1.02)

> BRT PHASE V ON WEBER AVENUE, MINER AVENUE, WILSON WAY, FREMONT STREET, FILBERT STREET, AND MAIN STREET CORRIDORS

SUMMARY EQUIPMENT LIST

PROJECT NO. PW1516 SHEET NO.

DESIGNED UNDER THE SUPERVISION OF: 12/19/2019

No. 048732 9/30/22 DATE

DEPARTMENT OF PUBLIC WORKS CITY OF STOCKTON, CALIFORNIA

DATE: DECEMBER 2019
SCALE: NONE
DRAWN BY: GMS
DESIGNED BY: TSW
CHECKED BY: EKC

DATE: \$3/20

APPROVED BY: DATE: DA

CALL TWO WORKING DAYS BEFORE YOU DIG

CA: 1-800-227-2600

CHECKED CITY APPROVAL
BY APPROVED BY DATE

1300 Clay Street, Suite 325 Oakland, California 94612 Phone: (510) 625—0712

KEVIN G. AGUIGUI R.C.E. No. 048732, EXP. 9/30/22

5365.35C