



NOTES:

1. 7'-0" (SEVEN) HIGH COMMERCIAL GRADE CURVED TOP SENTRY STYLE WROUGHT IRON FENCE WITH DOUBLE SWING GATES 16'-0"x7'-0"
2. SENTRY STYLE FENCE AND GATE SPECIFICATIONS:
 - A. RAILS: 1 $\frac{1}{2}$ "x1 $\frac{1}{2}$ "x11 GAUGE.
 - B. PICKETS: 1"x1"x15 GAUGE @ 5" O.C.
 - C. POSTS: 2 $\frac{1}{2}$ "x2 $\frac{1}{2}$ "x11 GAUGE @ 10'-0" O,C
 - D. GATE POSTS: 4"x4"x11 GAUGE
3. ALL WELDED STEEL CONSTRUCTION (UNLESS OTHERWISE NOTED).
4. 4-#4 VERTICAL WITH #3 HOOPS AT 12" O.C. (TYPICAL).
5. WELD CAPS ON ALL POST TUBING.
6. PRIME AND PAINT FENCE HUNTER GREEN.
7. ALL WELDS SHALL BE RE-GALVANIZED AND PROPERLY COATED.
8. INSTALL 12" WIDE x 4" DEPTH CONCRETE BAND (6" FROM CENTERLINE OF FENCE TO EACH SIDE) ALONG FENCE AND GATE ALIGNMENT.
9. 12" ϕ CONCRETE PIER.

TUBULAR STEEL FENCE DETAIL



REVISION NO. 1	APPROVED BY CITY ENGINEER: <i>[Signature]</i> DATE: 09/27/2016
SCALE NONE	SUPERSEDES DWG. DATED 11/25/03 DRAWING NO. M-6